

BX, Flex Connectors

Straight - Squeeze Type with Insulated Throat - Zinc Die Cast



Features


- Squeeze type straight with insulated throat

Applications

- Indoor use only
- In a dry location, use to connect flexible metallic conduit and steel AC cable to a steel outlet box, load center or other metal enclosure
- Suitable for: 1/2" steel flexible conduit, #14/2 metal conduit and #4-2 wire steel armored cable, 3/4" steel flexible metal conduit and #6-3 wire steel armored cable, 1" steel and reduced wall steel flexible metal conduit and #2-2 wire steel armored cable and 1-1/4" - 4" steel flexible metal conduit

Standard Material

- Zinc die cast



Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/Case	Inches			
						A	B (Min.-Max.)	C	Screws
151i	11001	1/2"	25	250	25	1.47	.74-.95	.40	1
152i	11011	3/4"	25	250	32	1.58	.88-1.11	.40	1
153i	11021	1"	10	100	20	1.75	1.14-1.38	.54	1
154i	11031	1-1/4"	10	100	29	1.91	1.42-1.65	.64	1
155i	11041	1-1/2"	5	50	20	2.09	1.68-1.94	.75	1
156i	11051	2"	10	40	21	2.34	2.08-2.56	.74	1