

# Rigid Conduit Bodies

## Threaded LB Type - Malleable Iron

### Features

- NPT tapered hubs
- Suitable for use in concrete

### Applications

- Provides access to conductors for pulling, splicing and maintenance

### Standard Material


- Malleable iron

### Standard Finish

- Zinc plated, aluminum enameled



UL Standard: 514A  
Fed. Spec. W-C 586D  
NEMA FB 1



Catalog Number	UPC	Size	Wire Size		Ship Case	Weight/Case	Inches		
			Max. Number	Max. Size			A	B	C
<b>LB1M</b>	20940	<b>1/2"</b>	---	---	10	7	4.56	2.06	1.31
<b>LB2M</b>	20950	<b>3/4"</b>	3	6 AWG	10	9	5.31	2.37	1.48
<b>LB3M</b>	20960	<b>1"</b>	3	4 AWG	5	6	6.25	2.63	1.75
<b>LB4M</b>	20970	<b>1-1/4"</b>	3	2 AWG	5	23	8.22	3.50	2.40
<b>LB5M</b>	20980	<b>1-1/2"</b>	3	1/0 AWG	10	26	8.22	3.75	2.40
<b>LB6M</b>	20990	<b>2"</b>	3	4/0 AWG	5	26	10.48	4.31	3.05
<b>LB7M</b>	21000	<b>2-1/2"</b>	3	300 MCM	1	10	13.75	4.45	4.38
<b>LB8M</b>	21010	<b>3"</b>	3	350 MCM	1	13	13.75	4.45	4.38
<b>LB9M</b>	21020	<b>3-1/2"</b>	3	500 MCM	1	22	16.75	5.80	5.63
<b>LB10M</b>	21030	<b>4"</b>	3	500 MCM	1	24	16.75	5.80	5.63