

Rigid Conduit Bodies

Threaded LL Type - Malleable Iron

Features

- NPT tapered hubs
- Suitable for use in concrete

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Malleable iron

Standard Finish

- Zinc plated, aluminum enameled



UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Catalog Number	UPC	Size	Wire Size		Internal Volume (in ³)	Ship Case	Weight/Case	Inches		
			Max. Number	Max. Size				A	B	C
LL1M	21140	1/2"	---	---	4.5	10	7	4.56	1.31	2.06
LL2M	21150	3/4"	3	6 AWG	7.5	10	9	5.31	1.62	2.23
LL3M	21160	1"	3	4 AWG	12.5	5	6	6.25	1.88	2.50
LL4M	21170	1-1/4"	3	2 AWG	32.3	5	23	8.22	2.50	3.40
LL5M	21180	1-1/2"	3	1/0 AWG	35.3	10	26	8.22	2.67	3.48
LL6M	21190	2"	3	4/0 AWG	73	5	26	10.48	3.29	4.07
LL7M	21200	2-1/2"	3	300 MCM	138	1	10	13.6094	3.9063	5.718
LL8M	21210	3"	3	350 MCM	170	1	13	13.875	4.75	5.875
LL9M	21220	3-1/2"	3	50 MCM	300	1	22	16.50	6.8125	7.125
LL10M	21230	4"	3	350 MCM	328	1	24	16.50	7.1875	7.125