

Rigid Conduit Bodies

Threaded LR Type - Malleable Iron

Features

- NPT tapered hubs
- Suitable for use in concrete

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Malleable iron

Standard Finish

- Zinc plated, aluminum enameled



UL Standard: 514A
Fed. Spec. W-C-586D
NEMA FB 1



Catalog Number	UPC	Size	Wire Size		Internal Volume (in ³)	Ship Case	Weight/Case	Inches		
			Max. Number	Max. Size				A	B	C
LR1M	21340	1/2"	---	---	4.5	10	7	4.56	1.31	2.06
LR2M	21350	3/4"	3	6 AWG	7.5	10	9	5.31	1.62	2.23
LR3M	21360	1"	3	4 AWG	12.5	5	6	6.25	1.88	2.50
LR4M	21370	1-1/4"	3	2 AWG	32.3	5	23	8.22	2.50	3.40
LR5M	21380	1-1/2"	3	1/0 AWG	35.3	10	26	8.22	2.67	3.48
LR6M	21390	2"	3	4/0 AWG	73	5	26	10.48	3.29	4.07
LR7M	21400	2-1/2"	3	300 MCM	138	1	10	13.75	4.45	4.38
LR8M	21410	3"	3	350 MCM	170	1	13	13.75	4.45	4.38
LR9M	21420	1/2"	3	350 MCM	300	1	22	16.75	5.80	5.63
LR10M	21430	4"	3	350 MCM	328	1	24	16.75	5.80	5.63