

FS and FD Cast Device Single Gang Boxes

FSC & FDC Type - Dual Hub - Heavy Duty Hot Dip Galvanized

Features

- Suitable for use in concrete
- Tapered threaded hubs-NPT
- Internal grounding screw
- Suitable for wet locations when used with cover and neoprene gasket (FSFDCG)

Applications

- For use in areas where boxes are exposed to harsh locations
- Provides opening for making splices
- Serves as a pull box for conductors
- Allows connection for branch conduit runs

Standard Material


- Malleable iron

Standard Finish

- Hot dip galvanized



Conforms to finish thickness
ASTM A123/123M
UL 514A
Fed. Spec. A-A-50563
CSA C22.2 No. 18.3
NEMA FB-1



Catalog Number	UPC	Size	Ship Case	Weight/Case	A	Inches B	C
FSC TYPE							
FSC1MHDG	01826	1/2"	10	26	6.08	2.94	2.20
FSC2MHDG	01813	3/4"	10	26	6.08	2.94	2.20
FSC3MHDG	01814	1"	10	26	6.08	2.94	2.20
FDC TYPE - DEEP							
FDC1MHDG	01815	1/2"	10	31	6.11	2.97	2.90
FDC2MHDG	01817	3/4"	10	31	6.11	2.97	2.90
FDC3MHDG	01819	1"	10	32	6.11	2.97	2.90