

# Universal Strut Clamps

## EMT and Rigid

### Features

- For use with EMT/Rigid and IMC conduit
- All screws - 5/16" x 1-1/4" slotted hex head

### Applications

- Use to support stationary pipe and tubing lines from strut channel

### Standard Material


- Steel

### Standard Finish

- Zinc plated

### Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014



Catalog Number	UPC	Size	Screw Size	Ship Case	Weight/Case	Inches	
						A	B
<b>2101</b>	41031	<b>1/2"</b>	1/4-20 x 1-1/4"	100	10	1.24	2.30
<b>2102</b>	41032	<b>3/4"</b>	1/4-20 x 1-1/4"	100	11	1.24	2.46
<b>2103</b>	41033	<b>1"</b>	1/4-20 x 1-1/4"	100	13	1.24	2.68
<b>2104</b>	41034	<b>1-1/4"</b>	1/4-20 x 1-1/4"	100	16	1.24	3.21
<b>2105</b>	41035	<b>1-1/2"</b>	5/16-18 x 1-1/2"	50	9	1.24	3.42
<b>2106</b>	41036	<b>2"</b>	5/16-18 x 1-1/2"	50	11	1.24	4
<b>2107</b>	41037	<b>2-1/2"</b>	5/16-18 x 1-3/4"	50	17	1.24	5
<b>2108</b>	41038	<b>3"</b>	5/16-18 x 1-3/4"	25	21	1.24	5.55
<b>2109</b>	41039	<b>3-1/2"</b>	5/16-18 x 1-3/4"	25	13	1.24	6
<b>2110</b>	41040	<b>4"</b>	5/16-18 x 1-3/4"	25	15	1.24	6.50