

Rigid Couplings

Compression Type - Malleable Iron

Features

- Compression type couplings
- Threadless
- Concrete tight
- Suitable for use with UL 6 Rigid Conduit

Applications

- Dry location only
- Use to join two lengths of unthreaded Rigid or IMC Conduit

Standard Material


- Malleable iron

Standard Finish

- Zinc plated

Applicable Third Party Standards

- UL Standard: UL 514B
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014



| Catalog Number | UPC | Size | Unit Carton | Ship Case | Weight/Case | Inches | |
|----------------|-------|---------------|-------------|-----------|-------------|--------|------|
| | | | | | | A | B |
| 251M | 85528 | 1/2" | 10 | 100 | 16 | 1.81 | 1.50 |
| 252M | 85529 | 3/4" | 10 | 100 | 24 | 1.87 | 1.62 |
| 253M | 85530 | 1" | 5 | 50 | 48 | 2.18 | 2 |
| 254M | 85531 | 1-1/4" | 5 | 50 | 86 | 2.62 | 2.37 |
| 255M | 85532 | 1-1/2" | --- | 12 | 125 | 2.68 | 2.62 |
| 256M | 85533 | 2" | --- | 5 | 160 | 3 | 3.31 |
| 257 | 12131 | 2-1/2" | --- | 5 | 260 | 5.75 | 3.93 |
| 258 | 12141 | 3" | --- | 3 | 300 | 5.72 | 4.66 |
| 259 | 12151 | 3-1/2" | --- | 2 | 350 | 6 | 5.20 |
| 260 | 12161 | 4" | --- | 2 | 400 | 6.81 | 5.75 |
| 260A | 01495 | 5" | --- | 1 | 9 | 6.86 | 6.10 |
| 260B | 01496 | 6" | --- | 1 | 12 | 8.14 | 6.81 |