

# Insulated Metallic Grounding Bushings

## With Aluminum Lug - 105°C Thermoplastic Liner - Zinc

### Features

- Liner is rated flame retardant to 105°C
- UL listed for use with copper or aluminum grounding conductor

### Applications


- Indoor or outdoor use
- Use with locknut to terminate service conduit to a cabinet
- Lug provided for bonding jumper to a neutral bus bar
- Round surface of bushing prevents damage to wire insulation
- Plastic liner prevents damage to wire insulation

### Standard Material

- Body - Zinc/plastic insulator
- Lug - Aluminum
- Clamping screw - Steel
- Set screws - Steel



E195122



Catalog Number	UPC	Size	Grounding Lug Wire Size		Unit Carton	Ship Case	Weight/Case	Inches	
			Min.	Max.				A	B
<b>321</b>	12930	<b>1/2"</b>	14	4	50	500	25	1.25	.50
<b>322</b>	12940	<b>3/4"</b>	14	4	50	500	35	1.50	.50
<b>323</b>	12950	<b>1"</b>	14	4	25	250	30	1.75	.56
<b>324</b>	12960	<b>1-1/4"</b>	14	4	20	200	34	2.12	.62
<b>325</b>	12970	<b>1-1/2"</b>	14	2	10	100	20	2.37	.75
<b>326</b>	12980	<b>2"</b>	14	2	10	100	35	2.81	.75
<b>327</b>	12990	<b>2-1/2"</b>	14	1/0	--	50	25	3.62	.93
<b>328</b>	13000	<b>3"</b>	14	1/0	---	10	6	4.18	.93
<b>329</b>	13010	<b>3-1/2"</b>	14	2/0	---	10	7	4.68	.93
<b>330</b>	13020	<b>4"</b>	6	250MCM	---	10	8	5.25	.93