

# Rigid Straps

## Snap-On Type - One Hole - Steel

### Features

- Snap-on type Rigid strap with one holes
- Greater load bearing capability
- Easy to install

### Applications

- Indoor or outdoor use
- Use to secure EMT, Rigid or IMC conduit to wood, masonry or where greater load bearing is required

### Standard Material


- Steel

### Standard Finish

- Zinc plated

### Applicable Third Party Standards

- UL Standard: UL 2239
- Fed. Spec: W-F-406E, W-F-406D
- NEMA: FB 1-2014



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches	
						A	B
<b>531A**</b>	15041	<b>1/4"</b>	100	1000	14	1.51	.562
<b>531B**</b>	15045	<b>3/8"</b>	100	1000	12	1.81	.562
<b>531</b>	15050	<b>1/2"</b>	50	500	17	1.91	.625
<b>532</b>	15060	<b>3/4"</b>	50	500	25	2.21	.75
<b>533</b>	15070	<b>1"</b>	25	250	18	2.57	.875
<b>534</b>	15080	<b>1-1/4"</b>	20	200	18	2.79	.88
<b>535</b>	15090	<b>1-1/2"</b>	20	200	31	3.69	.899
<b>536</b>	15100	<b>2"</b>	10	100	24	4.17	1.14
<b>517*</b>	15670	<b>2-1/2"</b>	---	50	21	5	1.28
<b>518*</b>	15680	<b>3"</b>	---	25	12	5.55	1.28
<b>519*</b>	15690	<b>3-1/2"</b>	---	25	17	6.37	1.28
<b>520*</b>	15700	<b>4"</b>	---	25	17	6.87	1.28
<b>520A**</b>	15702	<b>5"</b>	---	10	17	9	1.50
<b>520B**</b>	15704	<b>6"</b>	---	10	20	10.35	1.50

\*EMT and Rigid

\*\*Not UL Listed

WARNING: Some products included in this specification sheet may be subject to the warning requirements of California's Proposition 65. Please refer to your product packaging for more information.