

Parallel Conduit Support

Hot Dip Galvanized

Features

- Hot dip galvanized for added durability and corrosion protection
- Provides a secure connection and tight clamping action capable of withstanding heavy load

Applications

- Parallel conduit supports are used to mount EMT, Rigid or IMC conduit parallel to a beam, channel or angle support

Standard Material

- Malleable iron
- Galvanized steel hardware


Standard Finish

- Hot dip galvanized



E174011

Conforms to finish thickness
ASTM A123/123M
UL 2239
RoHS
NEMA FB1
Federal Spec. A-A-50553



Catalog Number	UPC	Size	Ship Case	Weight/ Case	Inches	
					A	B
1561HDG	83233	1/2"	50	27	2.80	1.42
1562HDG	83235	3/4"	50	28	2.99	1.47
1563HDG	83236	1"	50	30	3.19	1.54
1564HDG	86554	1-1/4"	25	18	3.39	2.01
1565HDG	86555	1-1/2"	25	21	3.62	2.01
1566HDG	86556	2"	25	27	4.37	2.87
1567HDG	86557	2-1/2"	10	15	5.12	3.23
1568HDG	86558	3"	10	18	5.79	4.06
1569HDG	86559	3-1/2"	10	20	6.26	4.53
1570HDG	86560	4"	10	23	6.46	4.61