

# Eaton BR2L125RP

Catalog Number: BR2L125RP

Eaton BR main lug loadcenter, Rainproof, furnished with hub closure plates, Main lug, 125 A, 6R, Aluminum, Cover included, NEMA 3R, Metallic, 10 kAIC, 2 Spaces, 4 Circuits, Three-wire, Single-phase



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton BR main lug loadcenter	BR2L125RP
<b>UPC</b>	<b>Product Length/Depth</b>
786689339418	9.5 in
<b>Product Height</b>	<b>Product Width</b>
3.3 in	4.5 in
<b>Product Weight</b>	<b>Certifications</b>
6.5 lb	UL 50
	UL 67

## Catalog Notes

Ground bar kit priced separately.  
Suitable for use as service equipment when no more than 2 service disconnecting mains are provided or when not used as lighting & appliance panelboard

## defaultTaxonomyAttributeLabel

### Amperage Rating

125 A

### Bus material

Aluminum

### Cover

Cover included

### Number of circuits

4

### Number of spaces

2

### Phase

Single-phase

### Used with

Type BR 1-inch breakers

### Voltage rating

120/240 V

### Wire size

#14-1/0 AWG Cu/Al

### Box size

6R

### Enclosure

NEMA 3R

### Enclosure material

Metallic

### Interrupt rating

10 kAIC

### Number of wires

3

## Resources

### Brochures

Loadcenters and Circuit Breakers

Type BR Arc Fault Circuit Breakers and Loadcenters

### Catalogs

Loadcenters and circuit breakers

### Specifications and datasheets

Eaton Specification Sheet - BR2L125RP



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)