

iq.ul.com

Surge Protective Devices
[guide info](#)

E314042

Schneider Electric USA, Inc.
Schneider Electric, SURGE PROTECTION BUSINESS, 1751 S 4800 W, Salt Lake City UT 84104

SSP03EMA10xx(c)*
Permanently Connected

| <u>SPD</u> <u>Type</u> | <u>Volts</u> <u>(V)</u> | <u>AC/DC</u> <u>DC PV</u> | <u>Phase</u> | <u>Amps</u> <u>(A)</u> | <u>Ambient</u> <u>Min(°C)</u> | <u>Ambient</u> <u>Max(°C)</u> | <u>Mode</u> | <u>VPR</u> <u>(Vpk)</u> | <u>MCOV</u> <u>(V)</u> | <u>In</u> <u>(kA)</u> | <u>SCCR</u> <u>(kA)</u> |
|---------------------------|----------------------------|------------------------------|--------------|---------------------------|----------------------------------|----------------------------------|-------------|----------------------------|---------------------------|--------------------------|----------------------------|
| 1 | 240/120 | AC | 3H | n/a | -35 | 85 | L-L | 1200 | 300 | 20 | 200 |
| | | | | | | | L-N | 700 | 150 | | |
| | | | | | | | L-G | 700 | 150 | | |
| | | | | | | | N-G | 600 | 150 | | |
| | | | | | | | H-L | 1200 | 420 | | |
| | | | | | | | H-N | 1000 | 270 | | |
| | | | | | | | H-G | 1000 | 270 | | |

Evaluated to: UL 1449 4th Ed. Rev: 2017-07-21
(c) - Where xx can be 10, 12, 16, 18, 20 (except for model SSP09EMAxxyy) or 24 (except for model SSP09EMAxxyy).
* - Complementary Listed EMI Filters (FOKY), E314042.

SPDs investigated for Type 1 applications are automatically suitable for Type 2 applications and may be marked for SPD Type 1 and/or Type 2 applications. SPDs only marked "SPD Type 2" are not suitable for Type 1 applications.
Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2015-04-30
Last Revised: 2017-10-24

© 2017 UL LLC

