

# **D-Series LED Floodlights**

**Stock Solutions** 

## Energy Savings with Style in Stock

The D-Series LED floodlights are the ideal stock solution for distributors looking for super efficient solutions offering the right set of configurations for everyday floodlighting needs. 16 of the most popular configurations are stocked, readily available and offer proven performance from a brand you can trust.

#### The Configurations You Need

D-Series LED Flood stock solutions offer the key configurations that contractors need for everyday floodlighting. All stock configurations feature a powerful lumen package with a wide flood (6X6) beam pattern in a dark bronze finish. Choose from 4000K or 5000K and a variety of mounting options including adjustable threaded knuckle, adjustable slipfitter or yoke mount.

#### **Energy and Maintenance Savings**

Combining up to 84% energy savings with up to 20 years of expected service life makes HID floodlight replacement a "no-brainer" when using D-Series LED floodlights.





#### **Quick Facts:**

- Replaces 70W to 400W HID floodlights
- 3,000 lumens to 21,000 lumens
- Super efficient up to 160 LPW
- All configurations include wide flood optic, 120-277V and dark bronze finish
- Made in North America
- 5-year warranty

Outdoor



### **D-Series LED Floodlights - Stock Solutions**

Luminaire	HID Replacement	Mounting	System Watts	Lumens	LPW	сст	Part Number	UPC
	70-100W	Threaded Knuckle	21	3,050	145	4000K	DSXF1 LED P1 40K	00190887243321
DSXF1	Metal Halide					5000K	DSXF1 LED P1 50K	00190887243314
DOVLI	150W		42	5,570	133	4000K	DSXF1 LED P2 40K	00190887243345
	Metal Halide					5000K	DSXF1 LED P2 50K	00190887243338
	175W	(1/2" NPT)	54	7,790	144	4000K	DSXF2 LED P1 40K	00190887243260
DSXF2	Metal Halide					5000K	DSXF2 LED P1 50K	00190887243253
DSVLS	250W Metal Halide		78	10,680	137	4000K	DSXF2 LED P2 40K	00190887243123
						5000K	DSXF2 LED P2 50K	00190887243284
	400W Metal Halide	Integral Slipfitter (2-3/8" O.D. tenon)	• 111	17,450	157	4000K	DSXF3 LED 6 P1 40K IS	00889804560213
				17,770	160	5000K	DSXF3 LED 6 P1 50K IS	00889804560190
		Yoke (16-3 SO cord)		17,450	157	4000K	DSXF3 LED 6 P1 40K YKC62	00889804560206
DOVED				17,770	160	5000K	DSXF3 LED 6 P1 50K YKC62	00889804560138
DSXF3		Integral Slipfitter (2 3/8″ OD tenon)	138	21,000	152	4000K	DSXF3 LED 6 P2 40K IS	00889804560114
				21,380	155	5000K	DSXF3 LED 6 P2 50K IS	00889804560084
		Yoke (16-3 SO cord)		21,000	152	4000K	DSXF3 LED 6 P2 40K YKC62	00889804560107
				21,380	155	5000K	DSXF3 LED 6 P2 50K YKC62	00889804560077

All products listed are standard with MVOLT, wide flood optics and dark bronze finish. If you require a more customized solution, we can quickly ship directly from our factory in Crawfordsville, Indiana.



Depth:	3.13" (8.0 cm)
Width:	8.88" (22.6 cm)
Height:	7.75" (19.8 cm)
Overall Height:	12.00" (30.5 cm)
Weight:	7.2 lbs. (3.3 kg)
EPA:	0.6 ft <sup>2</sup> (0.06 m <sup>2</sup> )

DSXF1 Knuckle for Threaded Pipe



Depth:	3.13" (8.0 cm)
Width:	12.88" (32.7 cm)
Height:	7.75" (19.8 cm)
Overall Height:	12.00" (30.5 cm)
Weight:	10.5 lbs. (4.8 kg)
EPA:	0.8 ft <sup>2</sup> (0.07 m <sup>2</sup> )

DSXF2 Knuckle for Threaded Pipe



Depth:	4.89" (12.4 cm)	
Width:	12.90" (32.8 cm)	
Height:	13.58" (34.5 cm)	
Overall Height:	16.60" (42.2 cm)	
Weight:	20 lbs. (9.1 kg)	
EPA:	1.4 ft <sup>2</sup> (0.13 m <sup>2</sup> )	
DSXF3 Yoke with SO Cord		



Depth:	4.89" (12.4 cm)
Width:	12.90" (32.8 cm)
Height:	13.58" (34.5 cm)
Overall Height:	20.80" (52.8 cm)
Weight:	21 lbs. (9.5 kg)
EPA:	1.4 ft <sup>2</sup> (0.13 m <sup>2</sup> )

DSXF3 Integral Slipfitter



DesignLights Consortium® (DLC) Premium qualified product and DLC qualified product. Not all versions of this product may be DLC Premium qualified or DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

Visit www.lithonia.com for more information

