









**Weatherproof Thermoplastic Cover
 For Flanged Inlets and Flanged Receptacles**

IP44
SUITABILITY  



Description		Catalog Number	
For use with 15 and 20A, 2 pole, 2 wire and 2 pole, 3 wire Insulgrip® flanged inlets and flanged receptacles below.		WP1	
Straight Blade, 2 pole, 3 wire			
Flanged Inlets		Flanged Receptacles	
	HBL5278C HBL5378C HBL5478C HBL5678C		HBL5279C HBL5379C HBL5479C HBL5679C
Twist-Lock®, 2 pole, 2 wire and 2 pole, 3 wire			
Flanged Inlets		Flanged Receptacles	
	HBL8815C HBL7524C HBL4716C HBL4586C HBL4786C		HBL8809C HBL7526C HBL4715C HBL4585C HBL4785C

**Weatherproof Thermoplastic Cover
 For Flanged Inlets and Flanged Receptacles**

Description		Catalog Number		
For use with 20 and 30A, 3, 4, and 5 wire Insulgrip flanged inlets and flanged receptacles below.		WP2		
Twist-Lock®, 2 pole, 3 wire; 3 pole, 4 wire; 4 pole, 4 wire; 4 pole, 5 wire Flanged Inlets				
	HBL2315	HBL2445	HBL2635	HBL2765
	HBL2325	HBL2455	HBL2645	HBL2775
	HBL2335	HBL2465	HBL2655	HBL2815
	HBL2345	HBL2515	HBL2715	HBL2825
	HBL2355	HBL2525	HBL2725	HBL2835
	HBL2415	HBL2535	HBL2735	HBL3325C
	HBL2425	HBL2615	HBL2745	HBL3334C
	HBL2435	HBL2625	HBL2755	HBL7408C
Flanged Receptacles				
	HBL2316	HBL2446	HBL2636	HBL2766
	HBL2326	HBL2456	HBL2646	HBL2776
	HBL2336	HBL2466	HBL2656	HBL2816
	HBL2346	HBL2516	HBL2716	HBL2826
	HBL2356	HBL2526	HBL2726	HBL2836
	HBL2416	HBL2536	HBL2736	HBL3326C
	HBL2426	HBL2616	HBL2746	HBL3335C
	HBL2436	HBL2626	HBL2756	HBL7409C



WP1



WP2



HBL7780

**Weatherproof Thermoplastic Cover
 For Flanged Inlets 50 Amp CS Series**

Description	Catalog Number
For use with 50A locking inlets with trimmed sides only.	HBL7780

Dimensions in Inches (mm)