

## 20 Amp, 125, 250 Volts and 277 Volts AC 2 Pole, 3 Wire, Grounding



HBL2321SW



HBL2321S




HBL2311



HBL2311ST



HBL2325SW



HBL2315

### Plugs

#### Watertight Safety-Shroud®

| Description                                | Cord Dia.          | Catalog Number   | IP66 SUITABILITY | UL Type 4x, 12   |
|--|--------------------|------------------|------------------|------------------|
| Black Valox® housing, white Valox® clamps. | .360"-.930" (9-24) | <b>HBL2311SW</b> | <b>HBL2321SW</b> | <b>HBL2331SW</b> |

#### Safety-Shroud®

| Description   | Cord Dia.          | Catalog Number  | IP20 SUITABILITY                |
|---|--------------------|-----------------|---------------------------------|
| Black and white nylon body, white Valox® shroud. Can be used with the Insulgrip Connector Bodies. | .360"-.930" (9-24) | <b>HBL2311S</b> | <b>HBL2321S</b> <b>HBL2331S</b> |

#### Insulgrip®

| Description  | Cord Dia.          | Catalog Number     | IP20 SUITABILITY                  |
|--|--------------------|--------------------|-----------------------------------|
| Black and white nylon.                               | .360"-.930" (9-24) | <b>HBL2311</b>     | <b>HBL2321</b> <b>HBL2331</b>     |
| Black and white nylon, spring termination            | .360"-.930" (9-24) | <b>HBL2311ST</b>   | <b>HBL2321ST</b> <b>HBL2331ST</b> |
| Corrosion resistant, yellow nylon.                   | .360"-.930" (9-24) | <b>HBL23CM11</b>   | <b>HBL23CM21</b> -                |
| All black nylon.                                     | .360"-.930" (9-24) | <b>HBL2311BK</b>   | <b>HBL2321BK</b> -                |
| All black nylon, spring termination                  | .360"-.930" (9-24) | <b>HBL2311STBK</b> | <b>HBL2321STBK</b> -              |
| Cord clamps with removable inserts. All black nylon. | .360"-.930" (9-24) | <b>HBL2311EBK</b>  | <b>HBL2321EBK</b> -               |

Note: See page B-52 for accessories.

#### Valise®

| Description                        | Cord Dia.               | Catalog Number    | IP20 SUITABILITY  | UL                | CSA |
|------------------------------------|-------------------------|-------------------|-------------------|-------------------|-----|
| Yellow nylon.                      | .325"-.720" (8.26-18.3) | <b>HBL2311VY</b>  | <b>HBL2321VY</b>  | <b>HBL2331VY</b>  |     |
| Corrosion resistant, yellow nylon. | .325"-.720" (8.26-18.3) | <b>HBL23CM11V</b> | -                 | -                 |     |
| Black nylon.                       | .325"-.720" (8.26-18.3) | <b>HBL2311VBK</b> | <b>HBL2321VBK</b> | <b>HBL2331VBK</b> |     |

Note: See page B-53 for accessories.

### Flanged Inlets

#### Watertight Safety-Shroud®

| Description  | Catalog Number   | IP66 SUITABILITY  | UL Type 4x, 12   |
|--|------------------|-------------------|------------------|
| Gray Valox® housing and flange.                              | <b>HBL2315SW</b> | <b>HBL2325SW</b>  | <b>HBL2335SW</b> |
| Gray Valox® housing and flange, reverse service (Not shown). | -                | <b>HBL2325SWR</b> | -                |

Note: See page B-56 for accessories.

#### Insulgrip®

| Description                      | Catalog Number   | IP20 SUITABILITY                  |
|----------------------------------|------------------|-----------------------------------|
| Nylon casing, back wired.        | <b>HBL2315</b>   | <b>HBL2325</b> <b>HBL2335</b>     |
| Nylon casing, spring termination | <b>HBL2315ST</b> | <b>HBL2325ST</b> <b>HBL2335ST</b> |

Note: See page B-52 for accessories.

See pages B-69 and B-70 for technical information on Twist-Lock and Watertight Safety-Shroud devices.  
See page B-74 for technical information on Valise® plugs and connectors.



HBL2315ST

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

|  |  |   |
|--|--|---|
|  |  |   |
| <b>20A 125V</b><br><b>NEMA L5-20P</b><br><b>1 HP</b> | <b>20A 250V</b><br><b>NEMA L6-20P</b><br><b>2 HP</b> | <b>20A 277V AC</b><br><b>NEMA L7-20P</b><br><b>2 HP</b> |

**HBLMITL** - For use with Watertight Safety-Shroud receptacles, see page B-41.

