



Catalog No. MGU322R

Description: 60A GD DISC 3P NONFUSE TYP3R 240V

UPC No 783164459630

Home > Safety Switches > General Duty

- Designed for residential and light commercial applications where duty is not severe.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type GD.
- Fusible and non-fusible switches available.
- Quick-make, quick-break mechanism (30-200 amp).
- 60/75°C conductor rating.

Representative Image

Descriptors

Category	General Duty
GO Schedule	131AM

Specifications

Voltage	240 Vac
Amperage	60
Poles	3
Wires	3
Fusing	Non-Fusible
Duty	General
Handle Style	Straight
Enclosure Type	NEMA 3R (Outdoor)
Wire Range	12-2
240 Vac, NEC Std, 1-ph	10.0 hp
240 Vac, NEC Std, 3-ph	15.0 hp
250 Vdc	10.0 hp

Classifications

CSA Certified	CUL
UL Listed	Yes

Dimensions

Height	13.7 in
Depth	3.9 in
Width	8.4 in
Weight	10.0 lb

Publications

Title	Publication No.	Publication Type
Midwest Safety Switch Quick Selection Guide		
Midwest Safety Switch Quick Selection Guide	MET-041	Application and Technical
Midwest Safety Switches Line Card		
	MEA-010	Brochures
residential to commercial. Our General Duty switches are designed for residential and light commercial applications where duty is not severe. The Heavy Duty switches are designed for commercial and industrial applications where safety and superior reliability are essential.		
Midwest Safety Switches		
reliable and easy to install	MET-029	Brochures
Safety Switch Outline Drawing		
60A Heavy Duty Disconnect, NEMA Type 3R Enclosure	1013093SH3	mensional

Additional Documentation: Visit our Publication Library to find technical documentation, time current curves, CSI Specifications and promotional literature.