Eaton DH362UCK

Catalog Number: DH362UCK

Eaton Heavy duty single-throw non-fused safety switch, Singlethrow, 60 A, NEMA 4X, Non-metallic, Non-Fusible, Three-pole, Three-wire, 10 at 240 Vac TD 1 Ph, 20 at 480 Vac TD 1 Ph, 25 at 600 Vac TD 1 Ph, 20 at 240 Vac TD 3 Ph.

General specifications



Catalog Number DH362UCK

Eaton heavy duty non-fusible safety switch

UPC

782114296028

Product Length/Depth

Product Height

15.46 in

19.38 in

Product Width

Product Weight

17 lb

11.3 in

Compliances Warranty

Eaton Selling Policy 25-000, one (1) year NEC 230.62 (C) Compliant Barrier

from the date of installation of the

Certifications Product or eighteen (18) months from the

date of shipment of the Product,

UL Listed

whichever occurs first. **Catalog Notes**

> Suitable for service entrance use with a neutral or ground lug kit installed



Photo is representative



Physical Attributes

Enclosure

NEMA 4X

Enclosure material

Non-metallic

Fuse configuration

Non-fusible

Number Of Poles

Three-pole

Number of wires

3

Type

Single-throw

Performance Ratings

Amperage Rating

60 A

HP rating - max

10 at 240 Vac TD 1 Ph, 20 at 480 Vac TD 1 Ph, 25 at 600 Vac TD 1 Ph, 20 at 240 Vac TD 3 Ph, 50 at 480 Vac TD 3 Ph, 60 at 600 Vac TD 3 Ph, 10 at 250 Vdc

NEMA rating

NEMA 4X (Non-Metallic)

Voltage rating

600 V

Miscellaneous

Product Category

Heavy Duty, Non-Fusible

Resources

Catalogs

Eaton's Volume 2—Commercial Distribution

Drawings

DIMENSION DWG 30-200A NON-METALLIC SWITCHES

Specifications and datasheets

Eaton Specification Sheet - DH362UCK

Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.











Eaton.com/socialmedia