



WPS Wallpaper Standard

FEATURES

- 0-10V dimming standard
- PowerSet feature allows for multiple "set and forget" lumen stops in each fixture
- FieldCCeT feature allows for multiple "set and forget" CCT options in each fixture
- FieldCCeT models controls ready
- Photocell standard (FieldCCeT models)

CERTIFICATIONS

- UL Listed for wet locations
- IP65 Rated
- DesignLights Consortium® 5.1 Premium Qualified - meets the requirements for the highest DLC qualification for efficacy and lumen maintenance

PERFORMANCE

- Rated lifetime:
 - L70: >54,000 hours
- 6,500 lm @ 45W
- 9,900 lm @ 71W
- 14,100 lm @ 99W
- 6,300 lm @ 46W
- 10,000 lm @ 73W
- 14,000 lm @ 102W
- 6,200/5,700/3,900/2,100 lm @ 44/40/28/15W
- 9,600/8,300/5,700/2,800 lm @ 68/59/40/20W
- 14,300/12,500/8,500/4,200 lm @ 102/90/60/30W
- 5000K CCT
- FieldCCeT: 50/40/3000K CCT
- CRI: >70

ELECTRICAL

- Input voltage: 120-277V, 277-480V; 120-347V
- 0-10V dimming with dim-to-off capability
- Power Factor: >0.9
- THD: <20%
- 120-347V 12VDC, 70mA (PS44 and PS68); 120-347V 12VDC, 100mA (PS102)

THERMAL

- -40°F to 104°F (-40°C to 40°C) operating temperature

CONSTRUCTION

- High impact polycarbonate lens
- Die-cast aluminum construction
- UV stabilized powder coated bronze finish
- Enclosure and hardware are corrosion resistant

WARRANTY

- 5 year limited warranty. Additional warranty options available. Contact EiKO for details

project name	type
catalog number	voltage
approved by	date



APPLICATIONS

- Industrial Parks
- Loading Docks
- Utility Sheds
- Entryways
- Walkways
- Storage Areas
- Security

CONFIGURATOR

MODEL	LUMEN PACKAGE	CRI/CCT	VOLTAGE	DIMMING	PHOTOCELL	FINISH
WPS : Standard Wallpaper	45W - 45W; 6,500 lm 71W - 71W; 9,900 lm 99W - 99W; 14,100 lm	750 - 70 CRI; 5000K	U - 120-277V	D - 0-10V Dimming	[Blank] - None	BZ - Bronze
	46W - 46W; 6,300 lm 73W - 73W; 10,000 lm 102W - 102W; 14,000 lm		V - 277-480V			
	PS44 - 44/40/28/15W PS68 - 68/59/40/20W PS102 - 102/90/60/30W	7FCCT - 70 CRI; 50/40/3000K	H - 120-347V		PC - Photocell	



PERFORMANCE SUMMARY

ORDER CODE	ITEM #	WATTS	NOMINAL LUMENS	CCT	CRI	DIMMING	VOLTS	REPLACES	DLC 5.1 PREMIUM
12104	WPS/45W/750/UD/BZ	45W	6,500	5000K	>70	0-10V	120-277V	70W	✓
12105	WPS/71W/750/UD/BZ	71W	9,900	5000K	>70	0-10V	120-277V	100W	✓
12106	WPS/99W/750/UD/BZ	99W	14,100	5000K	>70	0-10V	120-277V	150W	✓
12107	WPS/46W/750/VD/BZ	46W	6,300	5000K	>70	0-10V	277-480V	70W	✓
12108	WPS/73W/750/VD/BZ	73W	10,000	5000K	>70	0-10V	277-480V	100W	✓
12109	WPS/102W/750/VD/BZ	102W	14,000	5000K	>70	0-10V	277-480V	150W	✓

POWERSET AND FIELD CCT

12110	WPS/PS44/7FCCT/HD/PC/BZ	44/40/28/15W	6,200/5,700/3,900/2,100	50/40/3000K*	>70	0-10V	120-347V	70W	✓
12102	WPS/PS68/7FCCT/HD/PC/BZ	68/59/40/20W	9,600/8,300/5,700/2,800	50/40/3000K*	>70	0-10V	120-347V	100W	✓
12103	WPS/PS102/7FCCT/HD/PC/BZ	102/90/60/30W	14,300/12,500/8,500/4,200	50/40/3000K*	>70	0-10V	120-347V	150W	✓

*DLC 5.1 Premium @ 4000/5000K only

ACCESSORIES

ORDER CODE	ITEM #	DESCRIPTION
09966	PC1-4036-U	Photocell, Flush Mount, 120-277V
09967	PC1-4136-U	Photocell, Stem Mount, Side Lens, 120-277V
09968	PC1-4236-U	Photocell, Stem Swivel Mount, Side Lens, 120-277V
09969	PC1-4736-U	Photocell, Stem Swivel Mount, Top Lens, 120-277V

PRODUCT DIMENSIONS

