

Eaton XTOB250LC1

Catalog Number: XTOB250LC1

Eaton XT IEC bimetallic overload relay, 200-250A overload range, 140 mm Frame size, 1NO-1NC contact configuration, used with 225-300A, 10A trip type



General specifications

Product Name

Eaton XT IEC bimetallic overload relay

Catalog Number

XTOB250LC1

EAN

4015082100759

Product Length/Depth

5.67 in

Product Height

6.65 in

Product Width

5.04 in

Product Weight

5.5 lb

Compliances

CE Marked

RoHS Compliant

ATEX Compliant

Certifications

UL Listed

CSA Certified

IEC 60947

EN 60947

Catalog Notes

Short-circuit Type 1 rating is 500A and short-circuit Type 2 rating is 400A for separate mounting. The main current parameters are defined by the main current wiring that is used.



Powering Business Worldwide

Overload range

200-250 A

Frame size

140 mm

Brochures

[C440 Electronic Overload Relay](#)

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[XTOB_LC1 2D Drawing Xchange](#)

[XTOB_LC1 2D PDF](#)

[XTOB_LC1 AutoCAD 2D Footprint](#)

[XTOB_LC1 3D Model Xchange](#)

[XTOB_LC1 3D Inventor](#)

[XTOB_LC1 AutoCAD 2D Footprint \(mm\)](#)

Multimedia

[Overcurrent Protective Device Games - Fuses, Breakers and Contactors Explained](#)

Specifications and datasheets

[Eaton Specification Sheet - XTOB250LC1](#)

[Global Data Sheet - XTOB250LC1](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)