

# Eaton D4PR1T

Catalog Number: D4PR1T

Eaton General-purpose relay, D4 Series, Plug-In Relay, Plain cover  
QTY: 1, 24 V coil, SPDT contact configuration, 10 A, 250 Vac/30 Vdc resistive load, 7.5 A, 250 Vac/5 A, 30 Vdc inductive full load, 380 Vac/125 Vdc max. operating voltage

## General specifications




Photo is representative

### Product Name

Eaton General-purpose relay

### UPC

782114160589

### Product Height

0.1 in

### Product Weight

0.05 lb

### Catalog Number

D4PR1T

### Product Length/Depth

0.3 in

### Product Width

0.29 in

### Warranty

Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

### Compliances

RoHS Compliant  
CE Marked

### Certifications

UL Listed file E65657  
CSA file No. LR701519  
UL Listed file E1491  
cRUus

### Catalog Notes

Indicator lamp available. Consult sales office or customer support center for additional coil voltages.

## defaultTaxonomyAttributeLabel

### Amperage Rating

10A

### Cover

Plain

### Coil voltage

24 V

### Contact configuration

SPDT

### Inductive full load

7.5 A at 250 Vac, 5 A at 30 Vdc

### Quantity

1

### Resistive load

10 A, 250 Vac, 30 Vdc

### Series

D4

### Voltage - max

380 Vac/125 Vdc

## Resources

### Catalogs

[Eaton's Volume 7—Logic Control, Operator Interface and Connectivity Solutions](#)

### Drawings

[D4\\_R1 3D Inventor](#)

[D4\\_R1 2D Drawing Xchange](#)

[D4\\_R1 AutoCAD 2D Footprint \(mm\)](#)

[D4\\_R1 3D Model Xchange](#)

[D4\\_R1 AutoCAD 2D Footprint](#)

[D4\\_R1 2D PDF](#)

### Specifications and datasheets

[Eaton Specification Sheet - D4PR1T](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)