

# Eaton E49G31UP3

Catalog Number: E49G31UP3

Mini Complete Limit Switch, E49, Adjustable side rotary lever, Screw Terminals, 5A at 250 Vac, 5A at 30 Vdc, 5 mm-50 cm/s, 1NO-1NC



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton E49 mini metal limit switch	E49G31UP3
<b>UPC</b>	<b>Product Length/Depth</b>
786685102108	2.62 in
<b>Product Height</b>	<b>Product Width</b>
1.89 in	1.1 in
<b>Product Weight</b>	<b>Warranty</b>
0.42 lb	1 year
<b>Compliances</b>	
RoHS Compliant	

## defaultTaxonomyAttributeLabel

### Contact Rating

5A at 250 Vac, 5A at 30 Vdc

### Enclosure material

Cast zinc

### Actuator

Adjustable side rotary lever

### Connection

Screw terminal

### Contact configuration

1 NO-1 NC

### Series

E49

### Operating temperature - max

149 °F

### Operating temperature - min

23 °F

### Environmental rating

IP65

### Maximum AC current

5 A continuous

### Maximum DC current

5 A at 30 Vdc

### Operating speed

5 mm-50 cm/s

## Resources

### Brochures

[E49 Mini Metal Limit switches](#)

### Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

### Specifications and datasheets

[Eaton Specification Sheet - E49G31UP3](#)