

Eaton E59-M18C116D01-D1

Catalog Number: E59-M18C116D01-D1

Eaton iProx Sensor, E59, Straight, 18 mm, Unshielded, 360° viewable LED, M12, 300 mA at 6-48 Vdc, 4 pin, <3% sensing range, NPN/PNP auto configure, NO, 6-48 Vdc

General specifications



Product Name	Catalog Number
Eaton E59 iProx programmable inductive proximity sensor	E59-M18C116D01-D1
	UPC 782116303977
Product Length/Depth 2.73 in	Product Height 0.71 in
Product Width 0.71 in	Product Weight 0.1 lb
Warranty 1 year	Compliances CE Marked
Certifications UL Listed CSA Certified	

defaultTaxonomyAttributeLabel

Type

E59

Contact Rating

300 mA at 6-48 Vdc

Actuator function

Unshielded

Accuracy

< 3% sensing range

Enclosure material

303 stainless steel

Connection

M12

Contact configuration

NPN/PNP auto configure, NO

Series

E59

Environmental rating

NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13, IP67, IP69K

Temperature rating

-40 to 158 °F

Number of pins

4

Operating temperature - max

158 °F

Operating temperature - min

-40 °F

Maximum DC current

300 mA

Input voltage

6-48 Vdc

Size

18

LED indicator

360 ° viewable LED

Resources

Brochures

iProx sensors

Catalogs

Eaton's Volume 8—Sensing Solutions

Multimedia

We make what matters

Specifications and datasheets

Eaton Specification Sheet - E59-M18C116D01-D1

Protection

Auto reset



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia