

Eaton E59-M30A115A01-A1

Catalog Number: E59-M30A115A01-A1

Eaton iProx Sensor, E59, Straight, 30 mm, Shielded, 360° viewable LED, Dual key micro, 200 mA at 20-132 V, 3 pin, <1% sensing range, 2-wire AC, NO, 20-132V

General specifications



Photo is representative

Product Name	Catalog Number
Eaton E59 iProx programmable inductive proximity sensor	E59-M30A115A01-A1

UPC
782116183579

Product Length/Depth
2.92 in

Product Height
1.18 in

Product Width
1.18 in

Product Weight
0.7 lb

Warranty
1 year

Compliances
CE Marked

Certifications
UL Listed
CSA Certified

defaultTaxonomyAttributeLabel

Type

E59

Contact Rating

200 mA at 20-132 V

Actuator function

Shielded

Accuracy

< 1% sensing range

Enclosure material

303 stainless steel

Connection

Dual key micro

Contact configuration

2-wire AC, NO

Series

E59

Environmental rating

NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13,
IP67, IP69K

Temperature rating

-40 to 158 °F

Number of pins

3

Operating temperature - max

158 °F

Operating temperature - min

-40 °F

Maximum AC current

200 mA

Input voltage

20-132 V

Size

30 mm

LED indicator

360 ° viewable LED

Resources

Brochures

[iProx sensors](#)

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

Multimedia

[We make what matters](#)

Specifications and datasheets

[Eaton Specification Sheet - E59-M30A115A01-A1](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)