# Eaton JM60030-2MW14

## Catalog Number: JM60030-2MW14

Eaton Bussmann series JM modular fuse block, Multi-wire load-side lug, 30 A, 2-P, 120°C, 50 lb-inches max, Class J, Black, Box lug, 200 kAIC, 75 °C, DIN rail|Panel, 600 V





Catalog Number

Eaton Bussmann series JM modular fuse JM60030-2MW14

block

**UPC** 

051712620574

Product Length/Depth Product Height

3.4 in 2.3 in

Product Width Product Weight 2.2 in 0.31666667 lb

Warranty Compliances

Not Applicable RoHS Compliant

#### Certifications

ARO

European Pressure Equipment Directive

(PED) 97 /23 EC





#### Electrical rating

**Amperage Rating** 

30 A

Impulse withstand voltage

200 kA RMS symmetrical

Interrupt rating

200 kAIC

Short-circuit rating

200 kA RMS symmetrical

Torque rating

50 lb-in maximum

Voltage rating

600 V

### Physical details

Color

Black

Conductor material rated for

Both

Conductor temperature rating

75 °C

Conductor type

Stranded

Fuse type

Class J

**Number of Poles** 

Two-pole

Operating temperature - max

120 °C

Operating temperature - min

120 °C

#### General information

Connection

Box lug

Mounting method

Panel

DIN rail

Special features

Multi-Wire Load-Side Lug

#### Resources

Catalogs

JM60030-2MW14~2POLE J 600V30A PDFB 1-4

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - JM60030-2MW14



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia