

Cable, Cord and Hose Reels




Features and Benefits

inREACH™ Industrial Weatherproof Cord Reels

- UL Type 4 environmental listing
- 600V AC, SOW Type Cable
- Durable, corrosion resistant cast aluminum construction
- Multi-position guide arm can be mounted in two positions
- Ratchet lock can be disengaged in field for constant tension applications



HBLW45103




HBLW45123W



HBLW35143



HBLW45103



HBLIMB



HBLI340PB



HBLIMBJ



HBLI10BS

inREACH™ Industrial Weatherproof Cord Reels

Amps	Volts AC	Cable Length Feet (m)	Cable Type	Weight Lbs. (kg)	Yellow Reel	White Reel
10	600	45 (13.7)	16/3 SOW	23.6 (10.7)	HBLW45163	HBLW45163W
			16/4 SOW	25.6 (11.6)	HBLW45164	HBLW45164W
		35 (10.7)	16/3 SOW	22.5 (10.2)	HBLW35163	HBLW35163W
			16/4 SOW	23.1 (10.5)	HBLW35164	HBLW35164W
		25 (7.6)	16/3 SOW	21.4 (9.7)	HBLW25163	HBLW25163W
			16/4 SOW	21.8 (9.9)	HBLW25164	HBLW25164W
15	600	45 (13.7)	14/3 SOW	28.2 (12.8)	HBLW45143	HBLW45143W
			14/4 SOW	30.0 (13.6)	HBLW45144	HBLW45144W
		35 (10.7)	14/3 SOW	25.1 (11.4)	HBLW35143	HBLW35143W
			14/4 SOW	26.5 (12.0)	HBLW35144	HBLW35144W
		25 (7.6)	14/3 SOW	22.5 (10.2)	HBLW25143	HBLW25143W
			14/4 SOW	24.3 (11.0)	HBLW25144	HBLW25144W
18	600	80 (24.4)	12/3 SOW	97.5 (44.2)	—	HBLW80123W*
		75 (22.9)	12/4 SOW	107.4 (48.7)	—	HBLW75124W*
20	600	45 (13.7)	12/3 SOW	31.3 (14.2)	HBLW45123	HBLW45123W
			12/4 SOW	32.2 (14.6)	HBLW40124	HBLW40124W
		40 (12.2)	12/4 SOW	32.2 (14.6)	HBLW40124	HBLW40124W
			12/3 SOW	28.9 (13.1)	HBLW35123	HBLW35123W
		35 (10.7)	12/4 SOW	30.6 (13.9)	HBLW35124	HBLW35124W
			12/3 SOW	24.9 (11.3)	HBLW25123	HBLW25123W
25	600	75 (22.9)	10/3 SOW	103.8 (47.1)	—	HBLW75103W*
			10/4 SOW	116.2 (52.7)	—	HBLW75104W*
		40 (12.2)	10/3 SOW	33.3 (15.1)	HBLW40103	HBLW40103W
			10/4 SOW	34.2 (15.5)	HBLW35104	HBLW35104W
		35 (10.7)	10/3 SOW	31.7 (14.4)	HBLW35103	HBLW35103W
			10/4 SOW	34.2 (15.5)	HBLW35104	HBLW35104W
30	600	40 (12.2)	10/3 SOW	33.3 (15.1)	HBLW40103	HBLW40103W
			10/4 SOW	34.2 (15.5)	HBLW35104	HBLW35104W
		35 (10.7)	10/3 SOW	31.7 (14.4)	HBLW35103	HBLW35103W
			10/4 SOW	34.2 (15.5)	HBLW35104	HBLW35104W
		25 (7.6)	10/3 SOW	28.4 (12.9)	HBLW25103	HBLW25103W
			10/4 SOW	30.2 (13.7)	HBLW25104	HBLW25104W
40	600	45 (13.7)	8/3 SOW	106.5 (48.3)	—	HBLW4583W*
		60 (18.3)	8/3 SOW	123.2 (55.9)	—	HBLW6083W*
		45 (13.7)	8/4 SOW	122.8 (55.7)	—	HBLW4584W*
55	600	45 (13.7)	6/3 SOW	123.0 (55.8)	—	HBLW4563W*
		45 (13.7)	6/4 SOW	126.7 (57.5)	—	HBLW4564W*
14	600	45 (13.7)	12/8 SOW	107.4 (48.7)	—	HBLW45128W*
		45 (13.7)	14/12 SOW	113.5 (51.5)	—	HBLW451412W*

inREACH™ Accessories

Description	Weight Lbs. (kg)	Catalog Number
Mounting bracket	2.5 (1.1)	HBLIMB
Mounting bracket with junction box mount	3.0 (1.4)	HBLIMBJ
Mounting bracket	3.5 (1.6)	HBLIACMB*
Mounting bracket with junction box mount	4.0 (1.8)	HBLIACMBJ*
340° pivot base	3.5 (1.6)	HBLI340PB
Replacement stop	.2 (.09)	HBLI16BS HBLI14BS HBLI12BS HBLI10BS

Note: *Compatible with cord reel models marked with a single asterisk (*)