

15 and 20 Ampere, 125 Volts



15A 125V
NEMA 5-15R
UL CSA
0.5 HP



20A 125V
NEMA 5-20R
UL CSA
1 HP



Meets UL
Standard 943
Class A GFCI

SNAPConnect GFCI LED

Description	Color	Catalog Number	
SNAPConnect GFCI LED, self-grounding staple, requires connector below, sold separately.	Black	SNAPGF15BLK	SNAPGF20BLK
	Brown	SNAPGF15	SNAPGF20
	Gray	SNAPGF15GRY	SNAPGF20GRY
	Ivory	SNAPGF15I	SNAPGF20I
	Light Almond	SNAPGF15LA	SNAPGF20LA
	Red	SNAPGF15R	SNAPGF20R
	White	SNAPGF15W	SNAPGF20W



SNAPGF15GRY

SNAPConnect GFCI LED, Tamper and Weather Resistant

Description	Color	Catalog Number	
SNAPConnect GFCI TR/WR, self-grounding staple, requires connector below, sold separately.	Black	SNAPGFTW15BLK	SNAPGFTW20BLK
	Brown	SNAPGFTW15	SNAPGFTW20
	Gray	SNAPGFTW15GRY	SNAPGFTW20GRY
	Ivory	SNAPGFTW15I	SNAPGFTW20I
	Light Almond	SNAPGFTW15LA	SNAPGFTW20LA
	Red	SNAPGFTW15R	SNAPGFTW20R
	White	SNAPGFTW15W	SNAPGFTW20W

Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption. All GFCI receptacles are furnished with a matching color thermoplastic wallplate, 20 amp feed-through capability.



15A 125V
NEMA 5-15R
UL CSA
0.5 HP



20A 125V
NEMA 5-20R
UL CSA
1 HP



SNAPConnect USB Charger, Duplex Receptacles

Description	Color	Catalog Number	
SNAPConnect USB Charger, Tamper-Resistant Style Line® decorator duplex receptacle, 15 or 20 Amp, 125 Volt AC with one Type A & one Type-C USB port, 3 Amp up to 9 Volt USB output.	Black	SNAP15UACBK	SNAP20UACBK
	Brown	SNAP15UAC	SNAP20UAC
	Gray	SNAP15UACGY	SNAP20UACGY
	Ivory	SNAP15UACI	SNAP20UACI
	Light Almond	SNAP15UACLA	SNAP20UACLA
SNAPConnect USB charger with dual USB-C Ports	White	SNAP15UACW	SNAP20UACW
	Black	SNAP15UC	SNAP20UC
	Brown	SNAP15UCGY	SNAP20UCGY
	Gray	SNAP15UCI	SNAP20UCI
	Ivory	SNAP15UCLA	SNAP20UCLA
	Light Almond	SNAP15UCW	SNAP20UCW
	White		



15A 125V
NEMA 5-15R
UL CSA
0.5 HP



20A 125V
NEMA 5-20R
UL CSA
1 HP



SNAPConnect Surge Protection, Tamper-Resistant Receptacle with Power Indicating LED


Description	Color	Catalog Number	
SNAPConnect Surge suppression, Tamper-Resistant, smooth face, duplex receptacle.	Blue	SNAP5262S	SNAP5362S
	Gray	SNAP5262GYS	SNAP5362GYS
	Ivory	SNAP5262IS	SNAP5362IS
	Light Almond	SNAP5262LAS	SNAP5362LAS
	White	SNAP5262WS	SNAP5362WS




15A 125V
NEMA 5-15R
UL CSA
0.5 HP




20A 125V
NEMA 5-20R
UL CSA
1 HP



SNAP15UACLA



SNAP5262S



SNAPCTG

SNAPConnect Tester

Description	Catalog Number
Circuit Tester for SNAPConnect receptacle terminals, GFCI and standard receptacles.	SNAPCTG

Note: See page Tech-10 for Tamper-Resistant, Weather Resistant and LED Power Indicators descriptions.

Dimensions in Inches (mm)