



Slope Ceiling IC-Rated 1400 Lumen LED Downlights, Gen 4

Luminaires with a slope-specific design that are both powerful and efficient.

Juno Slope and Super Slope LED Downlights are the industry's first recessed LED luminaires designed specifically for slope ceiling applications. Now these unique luminaires are available with a brilliant 1400 lumens, making them even better suited to the higher installation heights typically found with slope ceilings.

Features include:

- Dedicated, IC-rated 6" new construction slope and super slope housings
- Ultra-efficient 21-watt consumption, providing nearly 35% energy savings compared to 32-watt CFLs
- State-of-the-art light engine with LEDs binned within a 3-step MacAdam Ellipse, exceeding ENERGY STAR® requirements
- Superior fixture-to-fixture color uniformity
- 90+ CRI ensures outstanding color rendering
- 50,000-hour service life



Slope LED



Super Slope LED



JUNO®

Juno® Slope Ceiling IC-Rated 1400 Lumen LED Downlights, Generation 4

Ultra-efficient luminaires designed specifically for slope ceiling applications

These luminaires produce over 1400 powerful lumens from less than 21 watts and are available with 2700K, 3000K, 3500K or 4000K CCT. Standard Slope LED downlights accommodate new construction, insulated or non-insulated ceilings with 2/12 to 6/12 pitch (9° to 27°) ... Super Slope accommodates 7/12 to 12/12 pitch (30° to 45°). ENERGY STAR® and California T24 certified when used with select LED light engines and trims.

6" Slope New Construction

For use in standard slope applications with 2/12 to 6/12 pitch (9° to 27°)



16 1/8" L x 9 1/8" W x 7 1/8" H
Ceiling cutout: 7 1/2" x 7 1/8"

Dedicated 6" Slope Ceiling LED new construction housing with integral light engine and choice of dimmable drivers. The eldoLED driver option delivers smooth and flicker-free deep dimming performance. Air-Loc® fully sealed housing does not require separate gasket. IC housing designed for use in IC or non-IC construction.



Example: IC926LED G4 14LM 27K 90CRI 120 FRPC

Series	Gen	Lumens	CCT	CRI	Voltage/Driver
IC926LED 6" Slope New Construction Housing	G4	14LM 1400 Lumens	27K 2700K 30K 3000K 35K 3500K 40K 4000K	90CRI 90 CRI	120 FRPC 120V Only; Forward Phase/ ELV Dimming MVOLT EZ1* Multi-Volt (120-277V) eldoLED 0-10V, 1% dim MVOLT EZ10* Multi-Volt (120-277V) eldoLED 0-10V, 10% dim

6" Super Slope New Construction

For use in super slope applications with 7/12 to 12/12 pitch (30° to 45°)



18 1/2" L x 9 1/8" W x 7 1/8" H
Ceiling cutout: 8 3/32" x 6 1/16"

Dedicated 6" Super Slope Ceiling LED new construction housing with integral light engine and choice of dimmable drivers. The eldoLED driver option delivers smooth and flicker-free deep dimming performance. Air-Loc® fully sealed housing does not require separate gasket. IC housing designed for use in IC or non-IC construction.



Example: IC928LED G4 14LM 27K 90CRI 120 FRPC

Series	Gen	Lumens	CCT	CRI	Voltage/Driver
IC928LED 6" Super Slope New Construction Housing	G4	14LM 1400 Lumens	27K 2700K 30K 3000K 35K 3500K 40K 4000K	90CRI 90 CRI	120 FRPC 120V Only; Forward Phase/ ELV Dimming MVOLT EZ1* Multi-Volt (120-277V) eldoLED 0-10V, 1% dim MVOLT EZ10* Multi-Volt (120-277V) eldoLED 0-10V, 10% dim

*A+ Capable

Refer to the specification sheet for the list of factory qualified dimmer model numbers.

Note: ENERGY STAR® and T24 certification is dependent on trim finish and LED color temperature. See housing spec sheet for specific information for each trim.



A+ Capable configurations support A+ Certified Solutions. A+ Certified solutions from Acuity Brands help you quickly and confidently select and implement lighting systems that are both compatible and consistent. Go to www.acuitybrands.com/APIus or contact your local Acuity Brands representative for more information.



All trademarks referenced are property of their respective owners. Specifications subject to change without notice. Printed in the U.S.A.

6" Slope LED Trims

Downlights



Downlight Baffle*

614 BWH	Black
614 BSC	Black
614 BABZ	Black
614 BBL	Black
614 WWH	White



Downlight Cone

620 CWH	Clear Alzak®
620 BWH	Black Alzak®
620 HZWH	Haze
620 HZSC	Haze
620 WWH	White
620 WHZWH	Wheat Haze
620 WHZABZ	Wheat Haze



Lensed



Baffle, Regressed
Frosted Dome Lens
6330 WWH White



Trim Ring Finishes

ABZ: Classic Aged Bronze
SC: Satin Chrome
WH: White
BL: Black

* Patented one piece design eliminates the unsightly seam on the long side of the baffle (US Patent 8,966,741).

6" Super Slope LED Trims

Downlights



Downlight Baffle*

604 BWH	Black
604 BSC	Black
604 BABZ	Black
604 BBL	Black
604 WWH	White



Downlight Cone

602 CWH	Clear Alzak®
602 BWH	Black Alzak®
602 HZWH	Haze
602 HZSC	Haze
602 WWH	White
602 WHZWH	Wheat Haze
602 WHZABZ	Wheat Haze



Lensed



Baffle, Regressed
Frosted Dome Lens
6033 WWH White



Trim Ring Finishes

ABZ: Classic Aged Bronze
SC: Satin Chrome
WH: White
BL: Black