PL-C/T

12PL-C/T/COR/32V-840/IF15/P/4P/DIM 10/1

Philips PLED 4-pin & 2-pin lamps are an affordable LED solution to replace compact flourescent lamps. The product provides a natural lighting effect for use in many lighting applications, and provides instant energy savings, making them an environmentally-friendly solution. Available as replacements for 13W, 26W and 32W compact fluorescent lamps.

Product data

General Information	
Cap-Base	GX24q
Nominal lifetime	50,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
EU RoHS compliant	Yes

Light Technical	
Color Code	840 [CCT of 4000K]
Beam Angle (Nom)	120 degree(s)
Luminous Flux	1,500 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	125.00 lm/W
Color Consistency	<6
Color rendering index (CRI)	82
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Line Frequency	20000-100000 Hz
Input Frequency	20000-100000 Hz
Power Consumption	12 W
Lamp Current (Max)	500 mA
Lamp Current (Min)	150 mA
Wattage Equivalent	32 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	25-55 V
UL Type	UL Type A

Temperature	
Ambient temperature range	-20 °C to 45 °C
T-Case Maximum (Nom)	25 °C

Controls and Dimming	
Dimmable	Yes

Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Plastic
Product Length	100 mm
Bulb Shape	PL-C;PL-T

PL-C/T

Approval and Application	
Energy Saving Product	Yes
Approval Marks	RoHS compliance UL certificate KEMA Keur certificate DLC compliance
Energy Consumption kWh/1000 h	- kWh
Energy Certifications	DLC Standard

Application Conditions	
can it be used in closed luminaires	Yes

Product Data	
Order product name	12PL-C/T/COR/32V-840/IF15/P/4P/DIM 10/1

Full product name	12PL-C/T/COR/32V-840/IF15/P/4P/DIM 10/1
Order code	929001820404
Material Nr. (12NC)	929001820404
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	046677476137
Numerator - Packs per outer box	10
EAN/UPC - Case	50046677476132

Dimensional drawing



Product	D1	D2	A1	A2	A3
12PL-C/T/COR/32V-840/ IF15/P/4P/DIM 10/1	24.3 mm	29 mm	99.9 mm	109.9 mm	125.5 mm

Photometric data



General uniform lighting - 12PL-C/T/COR/32V-840/IF15/P/4P/DIM 10/1



Spectral Power Distribution Colour - 12PL-C/T/COR/32V-840/ IF15/P/4P/DIM 10/1

PL-C/T

Photometric data



Light Distribution Diagram - 12PL-C/T/COR/32V-840/IF15/P/4P/DIM 10/1

Lifetime



Life Expectancy Diagram - 12PL-C/T/COR/32V-840/IF15/P/4P/DIM 10/1



Life Expectancy Diagram - 12PL-C/T/COR/32V-840/IF15/P/4P/DIM 10/1



Life Expectancy Diagram - 12PL-C/T/COR/32V-840/IF15/P/4P/DIM 10/1



Lumen Maintenance Diagram - 12PL-C/T/COR/32V-840/IF15/P/4P/DIM 10/1

PL-C/T

Lifetime



Lumen Maintenance Diagram - 12PL-C/T/COR/32V-840/IF15/P/4P/DIM 10/1

© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.