

Commercial and Hospital Grade, Standard



Features and Benefits

- Fed. Spec UL Listed, Hospital Grade
- Green power indicator and red trip indicator
- Patented AUTOGUARD® self test technology
- Flush, nylon face, back and side wired, multiple drive screws, self-grounding staple



GFR83I

SNAPGF83GRY

Hospital Grade ●

Rating	Color	Standard	Night Light Two LED Night Lights	Alarm
	Black	GFR82BLK	GFR82BKNL	GFR82BKB
	Brown	GFR82	GFR82NL	GFR82B
	Gray	GFR82GRY	GFR82GYNL	GFR82GYB
	Ivory	GFR82I	GFR82INL	GFR82IB
	Light Almond	GFR82LA	GFR82LANL	GFR82LAB
	Red	GFR82R	GFR82RNL	GFR82RB
	White	GFR82W	GFR82WNL	GFR82WB
	Black	GFR83BLK	GFR83BKNL	GFR83BKB
	Brown	GFR83	GFR83NL	GFR83B
	Gray	GFR83GRY	GFR83GYNL	GFR83GYB
	Ivory	GFR83I	GFR83INL	GFR83IB
	Light Almond	GFR83LA	GFR83LANL	GFR83LAB
	Red	GFR83R	GFR83RNL	GFR83RB
	White	GFR83W	GFR83WNL	GFR83WB

Hospital Grade ● SNAPConnect®

Rating	Color	Standard
	Black	—
	Brown	—
	Gray	—
	Ivory	SNAPGF82I
	Light Almond	SNAPGF82LA
	Red	SNAPGF82R
	White	SNAPGF82W
	Black	SNAPGF83BLK
	Brown	SNAPGF83
	Gray	SNAPGF83GRY
	Ivory	SNAPGF83I
	Light Almond	SNAPGF83LA
	Red	SNAPGF83R
	White	SNAPGF83W

SNAPConnect Right Angle Pigtailed Terminal

Description	Type	Catalog Number
Clear right angle terminal with 6 inch leads, 600V, #12 AWG THHN/THWN-2, Polycarbonate housing material.	Solid Stranded	SNAP1RNA SNAP2RNA
Clear right angle terminal with 6 inch leads #12 AWG THHN/THWN-2; Polycarbonate housing material with WAGO terminals.	Solid Stranded	SNAP1RNAM2 SNAP2RNAM2

Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption. All GFCI receptacles are furnished with a matching color thermoplastic wallplate, 20 amp feed-through capability.

Dimensions in Inches (mm)