

Heavy Duty GFCI Receptacles

Commercial Grade, Tamper-Resistant and Weather Resistant



Features and Benefits

- Patented shutter design for tamper-resistant protection
- Meets NEC® requirements for TR (406.12) and WR (406.9), UV and corrosion resistance for harsh and damp applications
- Patented AUTOGUARD® self test technology
- Protects against line and load reversal, no power to the face or downstream if device is miswired



GFTWR15WIG

GFRTW83R

Tamper-Resistant Weather Resistant

Rating	Color	Standard	Isolated Ground	SNAPConnect®	Right Angle Pigtailed Terminal for SNAPConnect
	Black	GFRTW15BLK	GFTWR15BKIG	SNAPGFTW15BLK	Clear right angle terminal with 6 inch leads, 600V, #12 AWG THHN/THWN-2, Polycarbonate housing material. Solid SNAP1RNA Stranded SNAP2RNA
	Brown	GFRTW15	GFTWR15IG	SNAPGFTW15	
	Gray	GFRTW15GRY	GFTWR15GYIG	SNAPGFTW15GRY	
	Ivory	GFRTW15I	GFTWR15IIG	SNAPGFTW15I	
	Light Almond	GFRTW15LA	GFTWR15LAIG	SNAPGFTW15LA	
	Orange	—	GFTWR15ORIG	—	
	Red	GFRTW15R	GFTWR15RIG	SNAPGFTW15R	
	White	GFRTW15W	GFTWR15WIG	SNAPGFTW15W	
	Black	GFRTW20BLK	GFTWR20BKIG	SNAPGFTW20BLK	
	Brown	GFRTW20	GFTWR20IG	SNAPGFTW20	
	Gray	GFRTW20GRY	GFTWR20GYIG	SNAPGFTW20GRY	
	Ivory	GFRTW20I	GFTWR20IIG	SNAPGFTW20I	
	Light Almond	GFRTW20LA	GFTWR20LAIG	SNAPGFTW20LA	
	Orange	—	GFTWR20ORIG	—	
	Red	GFRTW20R	GFTWR20RIG	SNAPGFTW20R	
	White	GFRTW20W	GFTWR20WIG	SNAPGFTW20W	

Hospital Grade ● Tamper-Resistant Weather Resistant

Rating	Color	Standard	Isolated Ground	SNAPConnect®	Right Angle Pigtailed Terminal for SNAPConnect
	Black	GFRTW82BLK	GFTWR82BKIG	—	Clear right angle terminal with 6 inch leads, 600V, #12 AWG THHN/THWN-2, Polycarbonate housing material. Solid SNAP1RNA Stranded SNAP2RNA
	Brown	GFRTW82	GFTWR82IG	—	
	Gray	GFRTW82GRY	GFTWR82GYIG	SNAPGFTW82GRY	
	Ivory	GFRTW82I	GFTWR82IIG	SNAPGFTW82I	
	Light Almond	GFRTW82LA	GFTWR82LAIG	SNAPGFTW82LA	
	Orange	—	GFTWR82ORIG	—	
	Red	GFRTW82R	GFTWR82RIG	SNAPGFTW82R	
	White	GFRTW82W	GFTWR82WIG	SNAPGFTW82W	
	Black	GFRTW83BLK	GFTWR83BKIG	SNAPGFTW83BLK	
	Brown	GFRTW83	GFTWR83IG	SNAPGFTW83	
	Gray	GFRTW83GRY	GFTWR83GYIG	SNAPGFTW83GRY	
	Ivory	GFRTW83I	GFTWR83IIG	SNAPGFTW83I	
	Light Almond	GFRTW83LA	GFTWR83LAIG	SNAPGFTW83LA	
	Orange	—	GFTWR83ORIG	—	
	Red	GFRTW83R	GFTWR83RIG	SNAPGFTW83R	
	White	GFRTW83W	GFTWR83WIG	SNAPGFTW83W	

Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption. All GFCI receptacles are furnished with a matching color thermoplastic wallplate, 20 amp feed-through capability.

Dimensions in Inches (mm)