



UGR Series 20A 250V Quick-Wire Acceptor Receptacle

By Killark
Catalog # [UGR0-20232QW](#)

20A 250V Quick-Wire Acceptor Receptacle



*Representative Image

Features

- Factory sealed chamber in UGR receptacle contains switch's arcing components.
- Spring loaded receptacle cover closes when plug is removed.
- Copper-free aluminum (less than 4/10 of 1%) alloy resists corrosion
- Electrostatically applied and baked powder epoxy/polyester finish
- ACCEPTOR® plugs conform to NEMA configurations, while it's "turn to engage" feature locks in plug and can be used to prevent accidental disengagement of critical equipment.
- Plugs for use with type S/SO/ST/STO heavy duty cord.

Specifications

Nema Rating	3, 7(C, D), 9(F, G)
Buy America(n) Qualified	Contact Manufacturer
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups F, G • Class III, Divisions 1 & 2

Conductor

Number Of Poles	2
Number Of Wires	3

Current

Amperage Rating	20 A
-----------------	------

General

Product Family	Plugs & Receptacles
UPC	783936125770
Type	Straight Blade
Receptacle Type	Delayed Action
Material	Aluminum, Copper Free (less than 4/10 of 1%)
Series	UGR Series

Logistics

Factory Sealed	Factory Sealed
----------------	----------------

Product Assets

- [Catalog \[English\]](#)
[Installation Manual \[English\]](#)