

iq.ul.com

Surge Protective Devices
guide info

E314042

Schneider Electric USA, Inc.
Schneider Electric, SURGE PROTECTION BUSINESS, 1751 S 4800 W, Salt Lake City UT 84104

SSP03EMA10xx(c)*
Permanently Connected

<u>SPD</u> <u>Type</u>	<u>Volts</u> <u>(V)</u>	<u>AC/DC</u> <u>DC PV</u>	<u>Phase</u>	<u>Amps</u> <u>(A)</u>	<u>Ambient</u> <u>Min(°C)</u>	<u>Ambient</u> <u>Max(°C)</u>	<u>Mode</u>	<u>VPR</u> <u>(Vpk)</u>	<u>MCOV</u> <u>(V)</u>	<u>In</u> <u>(kA)</u>	<u>SCCR</u> <u>(kA)</u>
1	240/120	AC	3H	n/a	-35	85	L-L	1200	300	20	200
							L-N	700	150		
							L-G	700	150		
							N-G	600	150		
							H-L	1200	420		
							H-N	1000	270		
							H-G	1000	270		

Evaluated to: UL 1449 4th Ed. Rev: 2017-07-21
(c) - Where xx can be 10, 12, 16, 18, 20 (except for model SSP09EMAxxyy) or 24 (except for model SSP09EMAxxyy).
* - Complementary Listed EMI Filters (FOKY), E314042.

SPDs investigated for Type 1 applications are automatically suitable for Type 2 applications and may be marked for SPD Type 1 and/or Type 2 applications. SPDs only marked "SPD Type 2" are not suitable for Type 1 applications.
Where a minimum ambient temperature is not specified, assume 0°C unless the product is marked otherwise or with an Outdoor use Environmental Rating. See Electrical Equipment for Use in Ordinary Locations (AALZ) for details regarding Environmental Ratings.

Report Date: 2015-04-30
Last Revised: 2017-10-24

© 2017 UL LLC

