

# Eaton 1250E-6504

Catalog Number: 1250E-6504

Eaton Enhanced 50 Series Photoelectric Sensor, Photoelectric, Right Angle, Sensor distance: 200 Ft., Fiberglass reinforced plastic enclosure, 3A max AC, SPDT Form C Relay, 3A at 240 Vac, 5 Pin Mini Connector, 12–240 Vdc 24–240 Vac input



## General specifications

Product Name	Catalog Number
Eaton Enhanced 50 photoelectric sensor	1250E-6504
UPC	Product Length/Depth
782116112715	1.91 in
Product Height	Product Width
4.16 in	1.81 in
Product Weight	Warranty
0.3375 lb	3 year
Compliances	
Contact Manufacturer	

## defaultTaxonomyAttributeLabel

### Contact Rating

3A at 240 Vac

### Enclosure material

Fiberglass reinforced plastic

### Operating mode

Thru-beam

### Connection

5-pin mini connector

### Contact configuration

SPDT form C relay

### Sensor type

Through beam

### Switch type

Photoelectric

### Input voltage

12-240 Vdc, 24-240 Vac

### LED indicator

Power on: yellow

Marginal gain: red

Output status: green

### Maximum AC current

3 A

### Operating temperature - max

131 °F

### Operating temperature - min

-13 °F

### Environmental rating

IP67, IP69K

## Resources

### Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

### Specifications and datasheets

[Eaton Specification Sheet - 1250E-6504](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)