


STRAIGHT BLADE DEVICES

SNAPConnect® Hospital Grade Receptacles

B
SECTION

15 and 20 Ampere, 125 Volts



SNAPConnect GFCI LED Hospital Grade ●

Description	Color	Catalog Number
Hospital Grade SNAPConnect GFCI LED, self-grounding staple, requires connector below, sold separately.	Black	—
	Brown	—
	Gray	—
	Ivory	SNAPGF82I
	Light Almond	SNAPGF82LA
	Red	SNAPGF82R
	White	SNAPGF82W
		SNAPGF83BLK SNAPGF83 SNAPGF83GRY SNAPGF83I SNAPGF83LA SNAPGF83R SNAPGF83W

SNAPConnect GFCI LED Hospital Grade ● Tamper and Weather Resistant

Description	Color	Catalog Number
Hospital Grade SNAPConnect GFCI TR/WR, self-grounding staple, requires connector below, sold separately.	Black	—
	Brown	—
	Gray	—
	Ivory	SNAPGFTW82I
	Light Almond	SNAPGFTW82LA
	Red	SNAPGFTW82R
	White	SNAPGFTW82W
		SNAPGFTW83BLK SNAPGFTW83 SNAPGFTW83GRY SNAPGFTW83I SNAPGFTW83LA SNAPGFTW83R SNAPGFTW83W

Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption. All GFCI receptacles are furnished with a matching color thermoplastic wallplate, 20 amp feed-through capability.



SNAPConnect USB Charger Hospital Grade ● Duplex Receptacles

Description	Color	Catalog Number
Hospital Grade SNAPConnect USB Charger, Tamper-Resistant Style Line® decorator duplex receptacle, 15 or 20 Amp, 125 Volt AC with one type A & one type-C USB port, 3 Amp up to 9 Volt USB output.	Black	SNAP8200UACBK
	Brown	SNAP8200UAC
	Gray	SNAP8200UACGY
	Ivory	SNAP8200UACI
	Light Almond	SNAP8200UACLA
	Red	SNAP8200UACR
	White	SNAP8200UACW
Hospital Grade SNAPConnect USB Charger, Tamper-Resistant Style Line decorator duplex receptacle, 15 or 20 Amp, 125 Volt AC with two type-C USB ports type-C USB port, 3 Amp up to 9 Volt USB output.	Black	SNAP8200UCBK
	Brown	SNAP8200UC
	Gray	SNAP8200UCGY
	Ivory	SNAP8200UCI
	Light Almond	SNAP8200UCLA
	Red	SNAP8200UCR
	White	SNAP8200UCW
		SNAP8300UACBK SNAP8300UAC SNAP8300UACGY SNAP8300UACI SNAP8300UACLA SNAP8300UACR SNAP8300UACW
		SNAP8300UCBK SNAP8300UC SNAP8300UCGY SNAP8300UCI SNAP8300UCLA SNAP8300UCR SNAP8300UCW



SNAPConnect Surge Protection Hospital Grade ● Tamper-Resistant Receptacle with Power Indicating LED

Description	Color	Catalog Number
Hospital Grade SNAPConnect Surge suppression, Tamper-Resistant, smooth face, duplex receptacle.	Blue	SNAP8262S
	Gray	SNAP8262GYS
	Ivory	SNAP8262IS
	Light Almond	SNAP8262LAS
	Red	SNAP8262RS
	White	SNAP8262WS
		SNAP8362S SNAP8362GYS SNAP8362IS SNAP8362LAS SNAP8362RS SNAP8362WS



SNAPConnect Right Angle Pigtailed Connector


Description	Wire Type	Catalog Number
Clear right angle terminal with 6 inch leads #12 AWG THHN/THWN-2; Polycarbonate housing material.	Solid Stranded	SNAP1RNA SNAP2RNA
Clear right angle terminal with 6 inch leads #12 AWG THHN/THWN-2; Polycarbonate housing material with WAGO terminals.	Solid Stranded	SNAP1RNAM2 SNAP2RNAM2
Clear right angle terminal with 6 inch leads #12 AWG THHN/THWN-2; Polycarbonate housing material. 250 Volts.	Solid Stranded	SNAP251RA SNAP252RA




SNAPGF83R



SNAPGFTW83I



SNAP8300UACW



SNAP8262S



SNAP1RNA

Dimensions in Inches (mm)