

Features and Benefits




Commercial Tamper and Weather Resistant GFCI Receptacles

- Patented shutter design for tamper-resistant protection
- Meets NEC® requirements for TR (517-18c) and WR (406.9), UV and corrosion resistance for harsh and damp applications
- Patented AUTOGUARD® self test technology
- Protects against line and load reversal, no power to the face or downstream if device is miswired



Hospital Grade ● Tamper-Resistant and Weather Resistant GFCI Receptacles



Description	Rating	Color	Catalog Number	
Standard, flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Black Brown Gray Ivory Light Almond Red White	GFRTW82BLK GFRTW82 GFRTW82GRY GFRTW82I GFRTW82LA GFRTW82R GFRTW82W	GFRTW83BLK GFRTW83 GFRTW83GRY GFRTW83I GFRTW83LA GFRTW83R GFRTW83W
Flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Black Brown Gray Ivory Light Almond Red White	GFTWRST82BKU GFTWRST82U GFTWRST82GYU GFTWRST82IU GFTWRST82LAU GFTWRST82RU GFTWRST82WU	GFTWRST83BKU GFTWRST83U GFTWRST83GYU GFTWRST83IU GFTWRST83LAU GFTWRST83RU GFTWRST83WU
Isolated Ground, flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Black Brown Gray Ivory Light Almond Orange Red White	GFTWRST82BKIG GFTWRST82IG GFTWRST82GYIG GFTWRST82IIG GFTWRST82LAIG GFTWRST82ORIG GFTWRST82RIG GFTWRST82WIG	GFTWRST83BKIG GFTWRST83IG GFTWRST83GYIG GFTWRST83IIG GFTWRST83LAIG GFTWRST83ORIG GFTWRST83RIG GFTWRST83WIG
SNAPConnect®, flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Black Brown Gray Ivory Light Almond Red White	— SNAPGFTW82GRY SNAPGFTW82I SNAPGFTW82LA SNAPGFTW82R SNAPGFTW82W	SNAPGFTW83BLK SNAPGFTW83 SNAPGFTW83GRY SNAPGFTW83I SNAPGFTW83LA SNAPGFTW83R SNAPGFTW83W

Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support applications because of the possibility of power interruption. All GFCI receptacles are furnished with a matching color thermoplastic wallplate, 20 amp feed-through capability. See page Tech-10 for Tamper-Resistant and Weather Resistant descriptions.

SNAPConnect Right Angle Pigtailed Connector

Description	Wire Type	General Use
Clear right angle terminal with 6 inch leads #12 AWG THHN/THWN-2; polycarbonate housing material.	Solid Stranded	SNAP1RNA SNAP2RNA
Clear right angle terminal with 6 inch leads #12 AWG THHN/THWN-2; polycarbonate housing material with WAGO terminals.	Solid Stranded	SNAP1RNAME2 SNAP2RNAME2

Note: For Assembled in USA products, must order connector with NA suffix.

NEC® is a registered trademark of the National Fire Protection Association (NFPA).



GFTWRST83WIG



GFRTW83BLK



GFTWRST82BKIG



SNAPGFTW83I



SNAP1RNA

Dimensions in Inches (mm)