

SWITCHED DISCONNECTS AND ENCLOSURES

Ratings Quick Reference Guide

Circuit-Lock® Switched Enclosures

Amp	Description	Phase	Poles	HP				Catalog Number
				120	240	480	600	
30	NEMA 1 Aluminum	1	2	2	5	10	15	HBL1372
	NEMA 1 Aluminum	3	3	3	7.5	15	20	HBL1379
	NEMA 1 Non-Metallic	1	2	2	5	10	15	HBL1392
	NEMA 1 Non-Metallic	3	3	3	7.5	15	20	HBL1389
	NEMA 3/3R Non-Metallic	1	2	2	5	10	15	HBL13R22
	NEMA 3/3R Non-Metallic	3	3	3	7.5	15	20	HBL13R23
	NEMA 3R Aluminum	1	2	2	5	10	15	HBL13R92
	NEMA 3R Aluminum	3	3	3	7.5	15	20	HBL13R89
	IP69K UL TYPE 4X Labelless Non-Metallic	3	3	1	7.5	15	15	HBLDS30
	IP69K UL TYPE 4X Labelless Non-Metallic	3	3	1	7.5	15	15	HBLDS30AC
	IP69K UL TYPE 4X Labelless Non-Metallic	3	3	1	7.5	15	15	HBLDS30NK
	IP69K UL TYPE 4X Labelless Non-Metallic	3	3	1	7.5	15	15	HBLDS30ACNK
	IP69K UL TYPE 4X Labelless Non-Metallic	3	3	1	5	10	10	HBLDS30ACNK
	UL TYPE 4X Labelless Non-Metallic	3	3	1	7.5	15	15	HBLDS30MQR
	UL TYPE 4X Labelless Non-Metallic	3	3	1	7.5	15	15	HBLDS30MQ5
	UL TYPE 4X Labelless Non-Metallic	3	3	1	7.5	15	15	HBLDS30MQR2
	IP69K UL TYPE 4X Stainless Steel	3	3	1	7.5	15	15	HBLDS3SS
	IP69K UL TYPE 4X Stainless Steel	3	3	1	7.5	15	15	HBLDS3SSAC
	IP69K UL TYPE 4X Stainless Steel	3	3	1	7.5	15	15	HBLDS3SSVFD
	UL TYPE 4X Stainless Steel	3	3	1	7.5	15	15	HBLDS3SSMQR
UL TYPE 4X Stainless Steel	3	3	1	7.5	15	15	HBLDS3SSMQ5	
IP69K UL TYPE 4X, 12 and IP69K Sloped, SS	3	3	1	7.5	15	15	HBLDS3SSR	
IP69K UL TYPE 4X, 12 and IP69K Sloped, SS	3	3	1	7.5	15	15	HBLDS3SSR2K	
IP69K UL TYPE 4X, 12 and IP69K Sloped, SS	3	3	1	7.5	15	15	HBLDS3SSRVFD	
IP69K UL TYPE 4X, 12 and IP69K Sloped, SS	3	3	1	7.5	15	15	HBLDS3SSRAC	
IP69K UL TYPE 4X, 12 and IP69K Sloped, SS	3	3	1	7.5	15	15	HBLDS3SSrMQR	
IP69K UL TYPE 4X, 12 and IP69K Sloped, SS	3	3	1	7.5	15	15	HBLDS3SSrMQ5	
IP69K UL TYPE 4X, 12 and IP69K Sloped, SS	3	3	1	7.5	15	15	HBLDS3SSrMQR2	
UL TYPE 4X Non-Metallic Fused Disconnect	3	3	1	7.5	15	20	FDS30	
60	NEMA 3R Aluminum	1	2	—	10	15	20	HBL16R92D
	NEMA 3R Aluminum	3	3	—	10	25	30	HBL16R93D
	IP69K UL TYPE 4X Non-Metallic	3	3	7.5	30	50	50	HBLDS60
	IP69K UL TYPE 4X Non-Metallic	3	3	7.5	30	50	50	HBLDS60AC
	IP69K UL TYPE 4X Stainless Steel	3	3	7.5	30	50	50	HBLDS6SS
	IP69K UL TYPE 4X Stainless Steel	3	3	7.5	30	50	50	HBLDS6SSAC
	IP69K UL TYPE 4X, 12 and IP69K Sloped, SS	3	3	7.5	30	50	50	HBLDS6SSR
	IP69K UL TYPE 4X, 12 and IP69K Sloped, SS	3	3	7.5	30	50	50	HBLDS6SSRVFD
	IP69K UL TYPE 4X, 12 and IP69K Sloped, SS	3	3	7.5	30	50	50	HBLDS6SSRAC
	UL TYPE 4X Non-Metallic Fused Disconnect	3	3	3	15	30	40	FDS60
100	IP69K UL TYPE 4X Non-Metallic	3	3	7.5	30	50	50	HBLDS100
	IP69K UL TYPE 4X Non-Metallic	3	3	7.5	30	50	50	HBLDS100AC
	IP69K UL TYPE 4X Stainless Steel	3	3	7.5	30	50	50	HBLDS10SS
	IP69K UL TYPE 4X Stainless Steel	3	3	7.5	30	50	50	HBLDS10SSAC
	IP69K UL TYPE 4X, 12 and IP69K Sloped, SS	3	3	7.5	30	50	50	HBLDS10SSR
	IP69K UL TYPE 4X, 12 and IP69K Sloped, SS	3	3	7.5	30	50	50	HBLDS10SSRVFD
	IP69K UL TYPE 4X, 12 and IP69K Sloped, SS	3	3	7.5	30	50	50	HBLDS10SSRAC
200	UL TYPE 4X, 12 Non-Metallic	—	—	10	75	150	200	HBLDS20
	UL TYPE 4X, 12 Stainless Steel	—	—	10	75	150	200	HBLDS20SS

Note: HP ratings apply to Jog and LED versions.



Dimensions in Inches (mm)