

# Affinity® AFB, AFF and AFO

Architectural LED Emergency Lights

## Tough but Stylish Emergency Lighting

The Affinity® LED emergency lights by Lithonia Lighting® are stylish and equally durable for indoor and outdoor use. These sconce-like emergency lights are compact, architecturally designed and suitable for cold and wet weather exposure.

Affinity offers field-adjustable forward- or wide-throw light distribution and normal on-off photocell control options. The blend of style, toughness, technology and performance makes Affinity® a solid choice for all types of emergency lighting applications requiring an attractive design.

### Features:

- Automatically performs monthly and annual testing with multi-status diagnostics functions
- Multiple finish choices include white, black, dark bronze, or silver
- Matching remotes available to be used with other battery sources
- UL wet location listed
- Optional cold weather battery



Small  
battery  
chargers

# Affinity® AFB, AFF and AFO LED Emergency Lights



	AFF	AFB	AFO
<b>Best Use</b>	Above or beside the door	Above or beside the door	Above or beside the door
<b>Mounting</b>	Wall and building-mount	Wall and building-mount	Wall and building-mount
<b>Height</b>	7.5' to 14' above ground	7.5' to 14' above ground	7.5' to 14' above ground
<b>Spacing</b>	Up to 70'	Up to 30'	Up to 30'
<b>Design</b>	Architectural low-profile	Architectural low-profile	Architectural low-profile Oval
<b>Housing/ Construction</b>	Die-cast aluminum housing with polycarbonate lens	Die-cast aluminum housing with polycarbonate lens	Die-cast aluminum housing with polycarbonate lens
<b>Color Options</b>	White, dark bronze, black and silver	White and dark bronze	White and dark bronze
<b>Light Distribution</b>	Field adjustable throw and wide throw	Wide throw	Wide throw
<b>Voltage</b>	120-347 VAC, 50/60Hz	120-347 VAC, 50/60Hz	120-277 VAC, 50/60Hz
<b>Lumens</b>	635 Lumens (EM); 635 Lumens (Normal on)	225 Lumens (EM); 225 Lumens (Normal on)	350 Lumens (EM); 1275 Lumens ( Normal on)
<b>Optics</b>	4,000 CCT	4,000 CCT	5,000 CCT
<b>Certification</b>	UL Listed. List and labeled to comply with Canadian Standards C22.2 No. 141-10. Meets UL 924, NFPA 101, NFPA 70-NEC, C22.2 CSA, California Energy Commission Title 20 section 1605.3 (W)(4), FCC and OSHA	UL Listed. List and labeled to comply with Canadian Standards C22.2 No. 141-10. Meets UL 924, NFPA 101, NFPA 70-NEC, C22.2 CSA, California Energy Commission Title 20 section 1605.3 (W)(4), FCC and OSHA	UL Listed. Meets UL 924, NFPA 101, NFPA 70-NEC, C22.2 CSA, CSA, California Energy Commission Title 20 section 1605.3 (W)(4), FCC and OSHA.
<b>Wet Location/ Cold Weather</b>	Wet location listed for unit 32°F to 122°F (0° to 50°). Unit with CW (cold weather) listed for -22°F to 122°F (-30° to 50°C). Remote listed for -40°F to 122°F (-40° to 50°C).	Wet location listed for unit 32°F to 122°F (0° to 50°). Unit with CW (cold weather) listed for -22°F to 122°F (-30° to 50°C). Remote listed for -40°F to 122°F (-40° to 50°C).	Wet location listed for unit 32°F to 122°F (0° to 50°). Unit with CW (cold weather) listed for -22°F to 122°F (-30° to 50°C)
<b>Battery</b>	Lithium iron phosphate (LTP)	Nicad or optional lithium iron phosphate (LTP)	Nicad
<b>Testing</b>	Manual, Remote Testing and Self-Testing/Diagnostics	Manual, Remote Testing and Self-Testing/Diagnostics	Manual and Self-Testing/Diagnostics
<b>Emergency Backup</b>	90-minutes	90-minutes	90-minutes
<b>Remote Versions/ Capability</b>	Remote capacity with remote versions available for use with other battery sources only	Remote capacity with remote versions available for use with other battery sources only	No remote capacity or remote version
<b>Controls</b>	Optional normally-off or normally-on with photocell	Optional normally-off or normally-on with photocell	Normally-on with photocell
<b>Warranty</b>	5-year limited warranty	5-year limited warranty	5-year limited warranty
<b>Application</b>	Commercial outdoor or indoor	Commercial outdoor or indoor	Commercial outdoor or indoor

Visit [www.lithonia.com](http://www.lithonia.com) for more information