

Features and Benefits



Meets UL
Standard 943
Class A GFCI

Commercial Standard Hospital Grade ● GFCI Receptacles

- Fed. Spec UL Listed, Hospital Grade
- Green power indicator and red trip indicator
- Patented AUTOGUARD® self test technology
- Flush, nylon face, back and side wired, multiple drive screws, self-grounding staple



15A 125V
NEMA 5-15R
UL CSA
0.5 HP



20A 125V
NEMA 5-20R
UL CSA
1 HP

Hospital Grade ● GFCI Receptacles

Description	Rating	Color	Catalog Number	
Standard, flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Black Brown Gray Ivory Light Almond Red White	GFR82BLK GFR82 GFR82GRY GFR82I GFR82LA GFR82R GFR82W	GFR83BLK GFR83 GFR83GRY GFR83I GFR83LA GFR83R GFR83W
Flush, nylon face, back and side wired, multiple drive screws, self-grounding staple. Assembled in U.S.A.	15 and 20A 125V AC	Black Brown Gray Ivory Light Almond Red White	GFR82BKU GFR82U GFR82GYU GFR82IU GFR82LAU GFR82RU GFR82WU	GFR83BKU GFR83U GFR83GYU GFR83IU GFR83LAU GFR83RU GFR83WU
Night Light two LED night lights, flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Black Brown Gray Ivory Light Almond Red White	GFR82BKNL GFR82NL GFR82GYNL GFR82INL GFR82LANL GFR82RNL GFR82WNL	GFR83BKNL GFR83NL GFR83GYNL GFR83INL GFR83LANL GFR83RNL GFR83WNL
Alarm, flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Black Brown Gray Ivory Light Almond Red White	GFR82BKB GFR82B GFR82GYB GFR82IB GFR82LAB GFR82RB GFR82WB	GFR83BKB GFR83B GFR83GYB GFR83IB GFR83LAB GFR83RB GFR83WB
SNAPConnect®, flush, nylon face, back and side wired, multiple drive screws, self-grounding staple.	15 and 20A 125V AC	Black Brown Gray Ivory Light Almond Red White	— — — SNAPGF82I SNAPGF82LA SNAPGF82R SNAPGF82W	SNAPGF83BLK SNAPGF83 SNAPGF83GRY SNAPGF83I SNAPGF83LA SNAPGF83R SNAPGF83W

*Note: GFCI type receptacles should not be used in critical care patient areas or for electrical life support equipment applications because of the possibility of power interruption.
All GFCI receptacles are furnished with a matching color thermoplastic wallplate, 20 amp feed-through capability.
Requires pigtailed connector see page N-15.*

NEC® is a registered trademark of the National Fire Protection Association (NFPA).

Dimensions in Inches (mm)



GFRST82WNL



GFR83R



GFR83INL



GFR83BKB



SNAPGF83GRY