

SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY PRO SERIES
ASSEMBLED LOAD CENTER. MAIN BREAKER WITH 30 1-INCH SPACES
ALLOWING MAX 48 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V
(200A) 22KAIC. SPECIAL FEATURES: COPPER BUS, GREY TRIM NEMA TYPE
1 ENCLOSURE FOR INDOOR USE.

General technical data	
configuration of the busbars	COPPER BUS
number of circuits in a trunking unit	48
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	200 A
voltage between phase and Ground (GND) rated value	120 V
voltage between phase and phase rated value	240 V
Model	
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY PRO SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	30
size of the circuit-breaker	200A
General product approval	
certificate of suitability	UL
General Product Approval	



[Miscellaneous](#)



Test Certificates	
Miscellaneous	Marine / Shipping
	
	
	
other	
Miscellaneous	Confirmation
Environmental Con- firmations	Environmental Con- firmations

last modified:

7/9/2021 

