



# KT-WPLED100-M2-8XX-VDIM

## ARCHITECTURAL FULL-CUTOFF LED WALL PACK

### DESCRIPTION

Architectural 100W Full-Cutoff LED Wall Pack | 120–277V Input | 4000–5000K | Medium Housing | Bronze Finish | Wide Optic Lens

### APPLICATION

Building mount for exterior illumination (perimeters, pathways, loading docks, and other general security lighting requirements)



### PRODUCT FEATURES

- Architectural full cutoff design that improves building appearance and optimizes functional light distribution
- Heavy duty die cast aluminum housing with (5) 1/2" threaded conduit hubs: (1) on back and (1) on all four sides
- Powered by Keystone 0–10V dimming LED drivers
- Dark Sky friendly performance that eliminates undesirable sky glow and glare
- Features one translucent 3/4" threaded plug with anti-yellowing agent for use with photocell accessory KT-WPLED-PS-UV-KO, sold separately
- Precision-crafted optical lens that provides wide distribution pattern ideal for increased fixture spacing and uniformity
- Covers footprint of mid-size HID wallpacks
- Ambient operating temperature: –40°C/–40°F to 50°C/122°F
- UL Certified for wet locations; IP65 rated
- Fixture impact rating IK08
- Power Factor: >0.95
- THD: <20%
- LED chip lifetime: L70 >100,000 hrs @ 25°C/77°F ambient fixture temperature
- Meets FCC Part 15, Part B, Class A standards for conducted and radiated emissions

### PRODUCT SPECIFICATIONS


Catalog Number	Wattage	Lumens	Lumens Below 90°	Dimming	CCT	Efficacy	CRI	Housing Color	Input Voltage	Rated Life	Legacy Equivalent
KT-WPLED100-M2-840-VDIM	100W	12500	12410	0–10V	4000K	125 lm/W	>80	Bronze	120–277V	50,000 hrs	400W MH
KT-WPLED100-M2-850-VDIM		13000	12900		5000K	130 lm/W					

# KT-WPLED100-M2-8XX-VDIM


## ARCHITECTURAL FULL-CUTOFF LED WALL PACK

### PHOTOMETRIC SPECIFICATIONS

#### ISOCANDELA PLOT



#### LUMINOUS INTENSITY DISTRIBUTION



#### FLUX DISTRIBUTION


Zone	Lumens	% Luminaire
<b>Forward Light</b>	8,446 lm	64.1%
0°–30°	1,534 lm	11.6%
30°–60°	4,104 lm	31.1%
60°–80°	2,553 lm	19.4%
80°–90°	255 lm	1.9%
<b>Back Light</b>	4,633 lm	35.1%
0°–30°	1,263 lm	9.6%
30°–60°	2,156 lm	16.4%
60°–80°	1,094 lm	8.3%
80°–90°	119 lm	0.9%
<b>Up Light</b>	102 lm	0.8%
90°–100°	13 lm	0.1%
100°–180°	89 lm	0.7%

BUG* Rating	
Asymmetrical Luminaire Types	
Type I, II, III, IV	B3 U5 G3
Quadrilateral Symmetrical Luminaire Types	
Type V, Area Light	B3 U5 G2

\* Backlight, Uplight, Glare


#### MOUNTING

Side view




#### LIGHT DISTRIBUTION PATTERN

Isometric view from above; Luminaire mounted at 20'




**KT-WPLED100-M2-8XX-VDIM**  
 ARCHITECTURAL FULL-CUTOFF LED WALL PACK

**PHYSICAL SPECIFICATIONS**



**GENERAL SETUP INSTRUCTIONS**

**GENERAL WIRING DIAGRAM**



**Caution:** Before installing, make certain that AC power to the fixture is off.

**Caution:** The electrical rating of this product is 120–277V. Installer must confirm that there is 120–277V at the fixture before installation.



# KT-WPLED100-M2-8XX-VDIM

## ARCHITECTURAL FULL-CUTOFF LED WALL PACK

### ACCESSORIES

#### SENSORS

Factory-Installable OR Field-Installable (field-installable purchased separately)

✓	SUFFIX*	CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
	/MW3	KTS-MW3-UV-KO-K1	Microwave Sensor Kit, Includes 120-277V input to 12V DC convertor & 12V input sensor head, IP65. Bi-Level Control with Adjustable Hold Time, Dim Level and Standby Time. Installs via standard 1/2in KO	843654134147	BKG-51
	/PS	KT-WPLED-PS-UV-KO	Dawn to Dusk PhotoCell for WallPack fixtures. Fits M1, M2, L1 housings. 120-277V Input. Install via standard 1/2in KO	843654129198	DLU-58



Microwave Sensor Kit  
KTS-MW3-UV-KO-K1

Dawn to Dusk PhotoCell  
KT-WPLED-PS-UV-KO

\* For factory installation of accessory, add suffix to fixture part number (see ordering examples and instructions on last page of spec sheet).

#### CORD SETS

Factory-Installable OR Field-Installable (field-installable purchased separately)

✓	SUFFIX*	CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
	/515P6	KT-CS-515P-6-18/3	Cord set for high bay; 125V NEMA 5-15P; straight blade plug; 6' SJTOW cable; 18/3 wire	843654140124	UKH-26
	/L515P6	KT-CS-L515P-6-16/3	Cord set for high bays; 250V NEMA L5-15P; twist lock plug; 6' SJTOW cable; 16/3 wire	843654140186	POC-82




Cord Sets

\* For factory installation of accessory, add suffix to fixture part number (see ordering examples and instructions on last page of spec sheet).  
**Note:** For cord sets not listed here, please contact your Keystone sales rep.

#### MOUNTS AND BRACKETS

Field-Installable / Field-Use ONLY (purchased separately)

✓	SUFFIX*	CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
	-	KT-WPLED-BP-M	Back Plate for Medium Size Wallpacks, Covers Legacy Style Large HID Housing Dimensions. Standard Bronze Color.	843654130613	CCJ-21



Back Plate  
KT-WPLED-BP-M

\* For factory installation of accessory, add suffix to fixture part number (see ordering examples and instructions on last page of spec sheet).  
**Note:** This is needed with EM - will be added when factory installing EM

(Accessories continued on next page)



# KT-WPLED100-M2-8XX-VDIM

## ARCHITECTURAL FULL-CUTOFF LED WALL PACK

### ACCESSORIES (continued)

#### SURGE PROTECTORS

Factory-Installable OR Field-Installable (field-installable purchased separately)

✓	SUFFIX*	CATALOG NUMBER	DESCRIPTION	UPC	EASY CODE
	/10KV	KTSP-10KV-C	External Surge Protector, compact design. Parallel Wiring, 120-277V Input, Max Peak Protection (10KV, 10KA)	843654129204	BUU-26



\* For factory installation of accessory, add suffix to fixture part number (see ordering examples and instructions on last page of spec sheet).



# KT-WPLED100-M2-8XX-VDIM

## ARCHITECTURAL FULL-CUTOFF LED WALL PACK

### ORDERING INFORMATION

CATALOG NUMBER	PACK QTY.	UPC	EASY CODE	DLC PRODUCT ID
KT-WPLED100-M2-840-VDIM	1	843654129075	VMR-18	PTXBVYH
KT-WPLED100-M2-850-VDIM	1	843654129082	OYW-93	PSRAUX5Y

### CATALOG NUMBER BREAKDOWN

# KT-WPLED100-M2-8XX-VDIM

1	2	3	4	5	6	7	8	9	10
<b>1 Keystone Technologies</b>	<b>2 Fixture Type</b>		<b>5 Size</b>		<b>6 Style</b>		<b>7 CRI</b>		
<b>2 Fixture Type</b>	WP	Wallpack	M	Medium	2	Full-Cutoff	8	>80	
<b>3 LED Lamp</b>	<b>8 CCT</b>		<b>9 Dimming</b>						
<b>4 Max Wattage</b>	40	4000K	VDIM	0-10V					
<b>5 Size</b>	50	5000K							
<b>6 Style</b>									
<b>7 CRI</b>									
<b>8 CCT</b>									
<b>9 Dimming</b>									
<b>10 Additional Options</b>									

### ORDERING EXAMPLES

FIXTURE WITH TWO FACTORY-INSTALLED ACCESSORIES\*

**KT-WPLED100-M2-8XX-VDIM /MW3/515P6**

FIXTURE WITH SINGLE FACTORY-INSTALLED ACCESSORY

**KT-WPLED100-M2-8XX-VDIM /MW3**

FIXTURE WITH NO FACTORY-INSTALLED ACCESSORIES

**KT-WPLED100-M2-8XX-VDIM**

#### KEYSTONE FIXTURE

CATALOG NUMBER
KT-WPLED100-M2-8XX-VDIM

#### SENSORS

✓	SUFFIX	CATALOG NUMBER
✓	/MW3	KTS-MW3-UV-KO-K1

#### CORD SETS

✓	SUFFIX	CATALOG NUMBER
✓	/515P6	KT-CS-515P-6-18/3

\* When ordering more than one factory-installed accessory, use multiple suffixes as shown in the ordering examples above.  
 Note: All accessories can also be ordered separately for field installation using just their regular Catalog Number, UPC, or Easy Code.