


Conduit Locknuts



Use:

Conduit locknuts are used for securing Rigid and IMC Conduits and other threaded connectors to a steel outlet box or metal enclosure.

Materials

- Steel


Finish

- Zinc Plated

RIGID CONDUIT

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Ctn/Case Qty/Qty	Case Wt.
			A	B	C		
Boxed							
131	70805-2	3/8"	1.12	0.09	1.00	100/1000	11.5
132	70810-6	1/2"	1.37	0.10	1.25	100/1000	11.4
133	70815-1	3/4"	1.75	0.12	1.56	100/1000	16.2
134	70820-5	1"	2.12	0.12	1.91	100/1000	27.2
149	70825-0	1 1/4"	2.43	0.12	2.16	50/500	18.9
150	70830-4	1 1/2"	2.93	0.12	2.68	50/500	25.2
151	70835-9	2"	3.56	0.17	3.25	40/400	29.3
152	70840-3	2 1/2"	4.18	0.17	3.95	30/300	44.4
153	70845-8	3"	5.37	0.17	5.00	25/250	43.0
154	70850-2	3 1/2"	2.93	0.12	2.68	25/125	18.3
155	70855-7	4"	3.56	0.17	3.25	20/100	26.0
156	70860-1	5"	4.18	0.17	3.95	10/30	23.5
157	70865-6	6"	5.37	0.17	5.00	10/30	26.5

Die-Cast Locknuts



Use:

Conduit locknuts are used for securing Rigid and IMC Conduits and other threaded connectors to a steel outlet box or metal enclosure.

- Single Cast Thread
- Fully Reversible
- Creates a 360° Ground path
- UL Listed Stand Alone for Rigid Conduit

Materials

- Zinc Die-Cast

Certification

UL E155411 SF LR57925

Standards

UL 514B CSA C22.2
NEMA FB-1
NEC Article 345 & 346

RIGID CONDUIT

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions		Ctn/Case Qty/Qty	Case Wt.
			A	B		
Boxed						
8450	08450-2	1/2"	1.10	0.14	100/1000	10.5
8451	08451-9	3/4"	1.35	0.14	100/1000	11.3
8452	08452-6	1"	1.68	0.18	100/1000	20.7
8453	08453-3	1 1/4"	2.06	0.21	50/500	16.0
8454	08454-0	1 1/2"	2.38	0.21	20/200	9.7
8455	08455-7	2"	2.92	0.21	25/250	17.8
8456	08456-4	2 1/2"	3.52	0.29	10/100	12.2
8457	08457-6	3"	4.12	0.29	10/100	17.0
8458	08458-3	3 1/2"	4.67	0.31	10/50	8.7
8459	08459-0	4"	5.25	0.31	10/50	10.0