


## Squeeze Connectors



### Use:

Squeeze connectors are used to terminate Flexible Metal Conduit to a knock-out in a dry location box or enclosure.

- Squeeze Type

### Materials:

- Zinc Die-Cast

### Certification:

UL E155411 SP LR57925

### Standards:

UL 514B CSA C22.2 No. 18  
NEMA FB-1 NEC Article 350


## BX • MC • FLEX

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			
<b>Boxed</b>								
8375	08375-3	3/8"	1.09	0.5	0.62	-	50/500	32.0
8380	08380-7	1/2"	1.50	0.5	0.99	-	25/250	21.6
8381	08381-4	3/4"	1.59	0.5	1.18	-	25/250	33.7
8382	08382-1	1"	1.75	0.5	1.45	-	10/100	21.0
8383	08383-8	1 1/4"	1.90	0.6	1.73	-	10/100	28.0
8384	08384-5	1 1/2"	2.00	0.6	2.00	-	5/50	18.0
8385	08385-2	2"	2.10	0.6	2.55	-	10/40	18.4
8386	08386-9	2 1/2"	1.75	0.5	1.45	-	5	1.5
8387	08387-6	3"	1.90	0.6	1.73	-	1/5	12.7
8388	08388-3	3 1/2"	2.00	0.6	2.00	-	1	1.7
8389	08389-0	4"	2.10	0.6	2.55	-	1	2.1
<b>Boxed w/ insulated throat</b>								
8390	08390-6	1/2"	1.50	0.5	0.99	-	25/250	21.6
8391	08391-3	3/4"	1.59	0.5	1.18	-	25/250	33.7
8392	08392-0	1"	1.75	0.5	1.45	-	10/100	21.0
8393	08393-7	1 1/4"	1.90	0.6	1.73	-	10/100	28.0
8394	08394-4	1 1/2"	2.00	0.6	2.00	-	5/50	18.0
8395	08395-1	2"	2.10	0.6	2.55	-	10/40	18.4
8396	08396-8	2 1/2"	1.75	0.5	1.45	-	5	9.0
8397	08397-5	3"	1.90	0.6	1.73	-	1/5	12.7
8398	08398-2	3 1/2"	2.00	0.6	2.00	-	1	1.7
8399	08399-9	4"	2.10	0.6	2.55	-	1	2.1

### Trade Size

Trade Size	For Cable Sizes
3/8"	For Regular or Reduced Wall Steel Flexible Metal Conduit. For 12-2 through 10-3 Steel or Aluminum armored cable. For 12-2 through 10-3 Interlocking Steel or Aluminum Metal Clad Cable.
3/4"	For Regular or Reduced Wall Steel or Aluminum Flexible Metal Conduit.
1/2"	For Regular or Reduced Wall Steel Flexible Metal Conduit. For 6-3 Steel or Aluminum Aromored Cable. For 6-3 Interlocking Steel or Aluminum Metal Clad Cable.

## Squeeze Connectors (Malleable Iron)



### Use:

Squeeze connectors are used to terminate Flexible Metal Conduit to a knock-out in a dry location box or enclosure.

- Squeeze Type

### Materials:

- Malleable Iron

### Certification:

UL E155411 SP LR57925

### Standards:

UL 514B CSA C22.2 No. 18  
NEMA FB-1 NEC Article 350

## BX • MC • FLEX

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			
<b>Boxed</b>								
9580	09580-0	1/2"	1.50	0.5	0.99	-	25/125	16.6
9581	09581-7	3/4"	1.59	0.5	1.18	-	20/100	16.7
9582	09582-4	1"	1.75	0.5	1.45	-	10/50	13.0
9583	09583-1	1 1/4"	1.90	0.6	1.73	-	10/50	20.0
9584	09584-8	1 1/2"	2.00	0.6	2.00	-	5/25	15.8
9585	09585-5	2"	2.10	0.6	2.55	-	20	11.4
9586	09586-2	2 1/2"	1.75	0.5	2.00	-	5	8.6
9587	09587-9	3"	1.90	0.6	1.73	-	5	10.1
9588	09588-6	3 1/2"	2.00	0.6	2.00	-	1	4.4
9589	09589-3	4"	2.10	0.6	2.55	-	1	6.6
<b>Boxed w/ insulated throat</b>								
9580I	99580-3	1/2"	1.50	0.5	0.99	-	25/125	16.8
9581I	99581-0	3/4"	1.59	0.5	1.18	-	20/100	16.9
9582I	99582-7	1"	1.75	0.5	1.45	-	10/50	13.1
9583I	99583-4	1 1/4"	1.90	0.6	1.73	-	10/50	20.1
9584I	99584-1	1 1/2"	2.00	0.6	2.00	-	5/25	15.9
9585I	99585-8	2"	2.10	0.6	2.55	-	20	21.6
9586I	99586-5	2 1/2"	1.75	0.5	1.45	-	5	8.7
9587I	99587-2	3"	1.90	0.6	1.73	-	5	10.2
9588I	99588-9	3 1/2"	2.00	0.6	2.00	-	1	4.5
9589I	99589-6	4"	2.10	0.6	2.55	-	1	6.7