



Clamp Type Connectors (NM Sheathed)



Clamp Type Connectors (Oval Type SE)



Use:

Clamp type connectors are used to terminate Nonmetallic Sheathed and Oval Type SE or USE Cables to a knock-out in a dry location box or enclosure.

- UL Listed Locknut
- Male Hub Threads NPS

Materials:

- Zinc Die-Cast

Certification:

UL E213494 / E155410

CS LR57925

Standards:


UL 514B

CSA C22.2 No. 18

NEMA FB-1

NEC Articles 336 & 338

2-Piece connectors



Use:

2-Piece clamp type connectors are used to terminate one or more Nonmetallic Sheathed Cables to a knock-out in a dry location box or enclosure. Also used in old work locations.

- No Locknut Required
- Butterfly Style

Materials:

- Steel

NM / SE CABLE

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Pcs/ Unit	Ctn/Case Qty/Qty	Case Wt.
			A	B	C			

Boxed

8470	08470-5	3/8"	0.80	1.17	0.39	-	100/1000	47.8
8471	08471-2	3/4"	0.94	1.67	0.42	-	50/500	44.1
8472	08472-9	1"	1.12	1.95	0.44	-	25/250	34.9
8473	08473-6	1 1/4"	2.25	1.31	0.60	-	10/100	28.1
8474	08474-3	1 1/2"	2.87	1.33	0.60	-	5/50	19.0
8475	08475-0	2"	3.50	1.57	0.74	-	10/40	21.5

Boxed

8366	08366-1	1 1/4"	1.25	2.18	0.61	-	10/100	19.0
8367	08367-8	1 1/2"	1.44	2.61	0.64	-	25	21.5
8368	08368-5	2"	1.59	2.95	0.78	-	5/25	21.5

Trade Size

3/8"

For Cable Sizes

For one or two 14-2 to 12-2 Nonmetallic Sheathed Cables or one 0.29" to 0.45" diameter Flexible Cord.

3/4"

For 10-3 to 8-2 Nonmetallic Sheathed and 8-3 to 4-3 Oval Service Entrance Cable and 8-3 to 6-3 Round Service Entrance Cable.

1"

For 10-3 to 4-3 Nonmetallic Sheathed and 6-3 to 4-3 Oval Service Entrance Cable and 6-3 to 2-3 Round Service Entrance Cable

1 1/4"

4-3 to 2-3 Nonmetallic Sheathed and 1.19" Service Entrance Cable.

1 1/2"

For 1.48" Service Entrance Cable.

NM / SE CABLE

Catalog Number	UPC No 0-87115	Trade Size	Nominal Dimensions			Ctn/Case Qty/Qty	Case Wt.
			A	B	C		

Boxed

9245	09245-8	1/2"	1.312	0.95	0.65	-	100/1000	55.0
9246	09246-5	3/4"-1"	1.75	1.25	0.76	-	50/500	39.5
9247	09247-2	1 1/4"	2.125	1.63	0.76	-	100/1000	55.0
9248	09248-9	1 1/2"	2.50	1.97	0.79	-	50/500	39.5