30 Amp, 480 and 600 Volts AC
2 Pole, 3 Wire, Grounding


IP20 SUITABILITY



Plugs

Description	Cord Dia.	30A 240V AC NEMA L25-30P	30A 480V AC NEMA L8-30P 5 HP	30A 600V AC NEMA L9-30P
		Catalog Number		
Black and white nylon.	.325"-.930" (8.25-24)	HBL2601	HBL2641	HBL2651

Note: See page C-53 for accessories.




HBL2651

Flanged Inlets

Description	Catalog Number		
Nylon casing, back wired.	HBL2605	HBL2645	HBL2655

Note: See page C-52 for accessories.



HBL2655

IP20 SUITABILITY



Connector Bodies

Description	Cord Dia.	30A 240V AC NEMA L25-30R	30A 480V AC NEMA L8-30R 5 HP	30A 600V AC NEMA L9-30R
		Catalog Number		
Black and white nylon.	.325"-.930" (8.25-24)	HBL2603	HBL2643	HBL2653

Note: See pages C-52 and C-53 for accessories.




HBL2653

Single Flush Receptacles

Description	Catalog Number		
Black nylon face, back and side wired.	HBL2600	HBL2640	HBL2650

Note: See page C-52 for accessories.




HBL2650

Flanged Receptacles

Description	Catalog Number		
Nylon casing, back wired.	—	HBL2646	HBL2656

Note: See page C-52 for accessories.
See page C-69 for technical information on Twist-Lock devices.



HBL2656

Dimensions in Inches (mm)