

Type: .	Date:
Job Name: .	
Contractor:	
Catalog No.:	
Notes:	

### LFL10 Series - 80W

## **Descriptions**

The LFL10 Series are powerful LED Area Lights ideal for outdoor applications such as exterior building lighting, roadways, loading docks, or parking areas. Compared to traditional area lighting, the slim design of these Ultra-Bright LED Area Lights makes them lighter in weight, easier to install. Unlike other Area Lights, the LFL10 can be mounted and wired without having to access inside the fixture making the installation process even faster. Pre-installed Photocell on all models and Adjustable Wattage on selected models. UL listed for Wet Locations. DLC 5.1 Premium Listed.

# **General Specifications**

	Spec	LFL10-80W-P				
	Input Voltage	120~277V				
Electrical	Wattage	80W				
	Power Factor	> 0.9				
	Lumens	11000 lm				
	Efficacy	142 lm/W				
Light	CRI	70+				
Output	Color Temp.	5000K				
Output	BUG	B2-U0-G2				
	Distribution Type	TYPE III				
	Equivalent	250W				
	Housing	ADC12 Die Cast Aluminum				
	Finish	UV Resistant Bronze Powder Coat Finish				
Physical	Lens Material	High Light Transmittance Polycarbonate  Lens				
	Ambient Operating Temp	-40°C / -40°F to 40°C / 104°F				
	Mount (Sold Separately)	Slip Fitter, Trunnion, Yoke, Post Mount				
Other	Certification	cULus E335594; DLC 5.1 Premium				


▶ Lifespan: 50,000 hrs ▶ Beam Angle: 90° x 115°

Warranty: 5 Year Limited Warranty

▶ Dimmable: 0-10V/PWM/VR ▶ UL listed for Wet Location

▶ Features:

- Pre-installed Photocell
















LFL10-SF LFL10-T LFL10-PM LFL10-YK \*Mounting Options (sold separately)


#### **Dimensions**



AxBxC:

80W: 12-5/8" x 12-1/4" x 3-1/4"

### **Photometrics**



Item No.	Description















LFL10 LED AREA LIGHT HOUSING ONLY, WITH PHOTOCELL, 80W 120~277V 5000K-BRONZE LFL10-80W-P LFL10-SF SLIP FITTER FOR LFL10 SERIES 8 LFL10-T TRUNNION MOUNT FOR LFL10 SERIES 8 LFL10-PM POST MOUNT FOR LFL10 SERIES 12 LFL10-YK-80 YOKE MOUNT FOR LFL10 80W-230W 12 **SFPMA** SLIP FITTER TO POST MOUNT ADAPTER FOR LFL10 SERIES 12











Type: .	Date:
Job Name: .	
Contractor:	
Catalog No.:	
Notes:	

### LFL10 Series - 100W

## **Descriptions**

The LFL10 Series are powerful LED Area Lights ideal for outdoor applications such as exterior building lighting, roadways, loading docks, or parking areas. Compared to traditional area lighting, the slim design of these Ultra-Bright LED Area Lights makes them lighter in weight, easier to install. Unlike other Area Lights, the LFL10 can be mounted and wired without having to access inside the fixture making the installation process even faster. Pre-installed Photocell on all models and Adjustable Wattage on selected models. UL listed for Wet Locations. DLC 5.1 Premium Listed.

# **General Specifications**

	Spec	LFL10-100W-P				
	Input Voltage	120~277V				
Electrical	Wattage	100W				
	Power Factor	> 0.9				
	Lumens	13125 lm				
	Efficacy	137 lm/W				
Light	CRI	70+				
Output	Color Temp.	5000K				
Output	BUG	B3-U0-G2				
	Distribution Type	TYPE III				
	Equivalent	400W				
	Housing	ADC12 Die Cast Aluminum				
	Finish	UV Resistant Bronze Powder Coat Finish				
Physical	Lens Material	High Light Transmittance Polycarbonate Lens				
	Ambient Operating Temp	-40°C / -40°F to 40°C / 104°F				
	Mount (Sold Separately)	Slip Fitter, Trunnion, Yoke, Post Mount				
Other	Certification	cULus E335594; DLC 5.1 Premium				

▶ Lifespan: 50,000 hrs
 ▶ Beam Angle: 90° x 115°

Warranty: 5 Year Limited Warranty


**Description** 

Dimmable: 0-10V/PWM/VRUL listed for Wet Location

▶ Features:

Item No.

- Pre-installed Photocell







SFPMA










LFL10-SF LFL10-T LFL10-PM LFL10-YK \*Mounting Options (sold separately)


#### **Dimensions**



AxBxC:

100W: 12-5/8" x 12-1/4" x 3-1/4"

#### **Photometrics**



	(F)	
9	ERTIFIED	















LFL10-100W-P LFL10 LED AREA LIGHT HOUSING ONLY, WITH PHOTOCELL, 100W 120~277V 5000K-BRONZE LFL10-SF SLIP FITTER FOR LFL10 SERIES 8 LFL10-T TRUNNION MOUNT FOR LFL10 SERIES 8 LFL10-PM POST MOUNT FOR LFL10 SERIES 12 LFL10-YK-80 YOKE MOUNT FOR LFL10 80W-230W 12 **SFPMA** SLIP FITTER TO POST MOUNT ADAPTER FOR LFL10 SERIES 12











Type:	Date:
Job Name: .	
Contractor:	
Catalog No.:	
Notes:	

# LFL10 Series - 150W (Adjustable Wattage Model)

## **Descriptions**

The LFL10 Series are powerful LED Area Lights ideal for outdoor applications such as exterior building lighting, roadways, loading docks, or parking areas. Compared to traditional area lighting, the slim design of these Ultra-Bright LED Area Lights makes them lighter in weight, easier to install. Unlike other Area Lights, the LFL10 can be mounted and wired without having to access inside the fixture making the installation process even faster. Pre-installed Photocell on all models and Adjustable Wattage on selected models. UL listed for Wet Locations. DLC 5.1 Premium Listed.

# **General Specifications**

	Spec	LFL10-150W-P				
	Input Voltage	120~277V				
Electrical	Wattage Range	50W/80W/100W/150W				
	Power Factor	> 0.9				
	Lumens Range	6650lm/10640lm/13300lm/20137lm				
	Efficacy	133 lm/W				
Light	CRI	70+				
, ,	Color Temp.	5000K				
Output	BUG B3-U0-G3					
	Distribution Type TYPE III					
	Equivalent	Up to 750W				
	Housing	ADC12 Die Cast Aluminum				
	Finish	UV Resistant Bronze Powder Coat Finish				
Physical	Lens Material	High Light Transmittance Polycarbonate Lens				
	Ambient Operating Temp	-40°C / -40°F to 40°C / 104°F				
	Mount (Sold Separately)	Slip Fitter, Trunnion, Yoke, Post Mount				
Other	Certification	cULus E335594; DLC 5.1 Premium				

▶ Lifespan: **50,000 hrs** 

▶ Beam Angle: 135° x 150°

▶ Warranty: 5 Year Limited Warranty


▶ Dimmable: 0-10V/PWM/VR

**▶ UL listed for Wet Location** 

▶ Features:

- Pre-installed Photocell

Adjustable Wattage:50W/80W/100W/150W





(h)

Adjustable Wattage
DIP Switch with Cover
KEEP COVER ON FOR WATERPROOF
















LFL10-SF LFL10-T LFL10-PM LFL10-YK \*Mounting Options (sold separately)


#### **Dimensions**



AxBxC:

150W: 12-5/8" x 12-1/4" x 3-1/4"

### **Photometrics**



Item No.	Description	CERTIFIED	A P	LUMILEDS	IP65	RóHS	LM79	Again	Std. Pkg.
LFL10-150W-P	LFL10 LED AREA L 50W-150W ADJUST		,		L,				1
LFL10-SF	SLIP FITTER FOR	LFL10 SERIE	S						8
LFL10-T	TRUNNION MOUN	T FOR LFL10	SERIES						8
LFL10-PM	POST MOUNT FOR	R LFL10 SERII	≣S						12
LFL10-YK-80	YOKE MOUNT FOR	R LFL10 80W-2	230W						12
SFPMA DESIGNED IN THE	SLIP FITTER TO P	OST MOUNT	ADAPTER I	FOR LFL10 SERII	ES				12







Type: _	Date:
Job Name: _	
Contractor: _	
Catalog No.: _	
Notes:	

### LFL10 Series - 230W

## **Descriptions**

The LFL10 Series are powerful LED Area Lights ideal for outdoor applications such as exterior building lighting, roadways, loading docks, or parking areas. Compared to traditional area lighting, the slim design of these Ultra-Bright LED Area Lights makes them lighter in weight, easier to install. Unlike other Area Lights, the LFL10 can be mounted and wired without having to access inside the fixture making the installation process even faster. Pre-installed Photocell on all models and Adjustable Wattage on selected models. UL listed for Wet Locations. DLC 5.1 Premium Listed.

# **General Specifications**

		15140 220W P				
	Spec	LFL10-230W-P				
	Input Voltage	120~277V				
Electrical	Wattage	230W				
	Power Factor	>0.9				
	Lumens	33457 lm				
	Efficacy	143 lm/W				
Light	CRI	70+				
	Color Temp.	5000K				
Output	BUG	B4-U0-G4				
	Distribution Type	TYPE III				
	Equivalent	1000W				
	Housing	ADC12 Die Cast Aluminum				
	Finish	UV Resistant Bronze Powder Coat Finish				
	1 N A-+ i - l	High Light Transmittance Polycarbonate				
Physical	Lens Material	Lens				
	Ambient Operating Temp	-40°C / -40°F to 40°C / 104°F				
	Mount (Cold Congretaly)	Slip Fitter, Trunnion,				
	Mount (Sold Separately)	Yoke, Post Mount				
Other	Certification	cULus E335594; DLC 5.1 Premium				

▶ Lifespan: 50,000 hrs

▶ Beam Angle: 115° x 145°

Warranty: 5 Year Limited Warranty

▶ Dimmable: 0-10V/PWM/VR ▶ UL listed for Wet Location

▶ Features:


- Pre-installed Photocell





LFL10-SF LFL10-T LFL10-PM LFL10-YK \*Mounting Options (sold separately)


#### **Dimensions**



AxBxC:

230W: 12-5/8" x 14-3/4" x 3-1/4"

### **Photometrics**



ltem No.	Description	CERTIFIED	DLC PREMIUM	PHILIPS LUMILEDS IP65	ROHS	<b>-∵</b> LM79	5	Std. Pkg.

LFL10-230W-P LFL10 LED AREA LIGHT HOUSING ONLY, WITH PHOTOCELL, 230W 120~277V 5000K-BRONZE 1 LFL10-SF SLIP FITTER FOR LFL10 SERIES 8 LFL10-T TRUNNION MOUNT FOR LFL10 SERIES 8 POST MOUNT FOR LFL10 SERIES LFL10-PM 12 LFL10-YK-80 YOKE MOUNT FOR LFL10 80W-230W 12 SLIP FITTER TO POST MOUNT ADAPTER FOR LFL10 SERIES **SFPMA** 









Туре:	 Date:
Job Name:	
Contractor:	
Catalog No.:	
Notes:	

# LFL10 Series - 300W (Adjustable Wattage Model)

## **Descriptions**

The LFL10 Series are powerful LED Area Lights ideal for outdoor applications such as exterior building lighting, roadways, loading docks, or parking areas. Compared to traditional area lighting, the slim design of these Ultra-Bright LED Area Lights makes them lighter in weight, easier to install. Unlike other Area Lights, the LFL10 can be mounted and wired without having to access inside the fixture making the installation process even faster. Pre-installed Photocell on all models and Adjustable Wattage on selected models. UL listed for Wet Locations. DLC 5.1 Premium Listed.

# **General Specifications**

	Spec	LFL10-300W-P
Electrical	Input Voltage	120~277V
	Wattage Range	150W/200W/240W/300W
	Power Factor	> 0.9
Light Output	Lumens Range	21600lm/28800lm/34560lm/41466lm
	Efficacy	144 lm/W
	CRI	70+
	Color Temp.	5000K
	BUG	B5-U0-G4
	Distribution Type	TYPE III
	Equivalent	Up to 1000W
Physical	Housing	ADC12 Die Cast Aluminum
	Finish	UV Resistant Bronze Powder Coat Finish
	Lens Material	High Light Transmittance Polycarbonate Lens
	Ambient Operating Temp	-40°C / -40°F to 40°C / 104°F
	Mount (Sold Separately)	Slip Fitter, Trunnion,
		Yoke, Post Mount
Other	Certification	cULus E335594; DLC 5.1 Premium

▶ Lifespan: 50,000 hrs

▶ Beam Angle: 125° x 150°

▶ Warranty: 5 Year Limited Warranty


▶ Dimmable: 0-10V/PWM/VR

> UL listed for Wet Location

▶ Features:

- Pre-installed Photocell

- Adjustable Wattage: 150W/200W/240W/300W






Adjustable Wattage DIP Switch with Cover KEEP COVER ON FOR WATERPROOF

DHILLIDS




LFL10-SF LFL10-T LFL10-PM LFL10-YK \*Mounting Options (sold separately)

#### **Dimensions**



300W: 12-5/8" x 17-7/8" x 3-1/2"

## **Photometrics**



Item No.	Description CERTIFIED LUMILEDS IP65 ROHS LM79	Std. Pkg.
LFL10-300W-P	LFL10 LED AREA LIGHT HOUSING ONLY, WITH PHOTOCELL, 150W-300W ADJUSTABLE, 120~277V 5000K-BRONZE	1
LFL10-SF	SLIP FITTER FOR LFL10 SERIES	8
LFL10-T	TRUNNION MOUNT FOR LFL10 SERIES	8
LFL10-PM	POST MOUNT FOR LFL10 SERIES	12
LFL10-YK-300	YOKE MOUNT FOR LFL10 300W-400W	10
SFPMA DESIGNED IN THE	SLIP FITTER TO POST MOUNT ADAPTER FOR LFL10 SERIES	12

TABLE WAL







Туре:	Date:
Job Name:	
Contractor:	
Catalog No.:	
Notes:	

# LFL10 Series - 400W (Adjustable Wattage Model)

## **Descriptions**

The LFL10 Series are powerful LED Area Lights ideal for outdoor applications such as exterior building lighting, roadways, loading docks, or parking areas. Compared to traditional area lighting, the slim design of these Ultra-Bright LED Area Lights makes them lighter in weight, easier to install. Unlike other Area Lights, the LFL10 can be mounted and wired without having to access inside the fixture making the installation process even faster. Pre-installed Photocell on all models and Adjustable Wattage on selected models. UL listed for Wet Locations. DLC 5.1 Premium Listed.

# **General Specifications**

	Spec	LFL10-400W-P
Electrical	Input Voltage	120~277V
	Wattage Range	230W/300W/350W/400W
	Power Factor	> 0.9
Light Output	Lumens Range	32430lm/42300lm/49350lm/56047lm
	Efficacy	141 lm/W
	CRI	70+
	Color Temp.	5000K
	BUG	B5-U0-G5
	Distribution Type	TYPE III
	Equivalent	Up to 1200W
Physical	Housing	ADC12 Die Cast Aluminum
	Finish	UV Resistant Bronze Powder Coat Finish
	Lens Material	High Light Transmittance Polycarbonate Lens
	Ambient Operating Temp	-40°C / -40°F to 40°C / 104°F
	Mount (Sold Separately)	Slip Fitter, Trunnion, Yoke, Post Mount
Other	Certification	cULus E335594; DLC 5.1 Premium

▶ Lifespan: **50,000 hrs** 

▶ Beam Angle: 120° x 145°

▶ Warranty: 5 Year Limited Warranty


▶ Dimmable: 0-10V/PWM/VR

**▶ UL listed for Wet Location** 

▶ Features:

- Pre-installed Photocell

Adjustable Wattage:230W/300W/350W/400W






Adjustable Wattage
DIP Switch with Cover
KEEP COVER ON FOR WATERPROOF

**PHILIPS** 




LFL10-SF LFL10-T LFL10-PM LFL10-YK \*Mounting Options (sold separately)

#### **Dimensions**



400W: 12-5/8" x 22-3/8" x 3-1/2"

### **Photometrics**



Item No.	Description CERTIFIED PARTY LUMILEDS 1965 ROHS LM79	Std. Pkg.
LFL10-400W-P	LFL10 LED AREA LIGHT HOUSING ONLY, WITH PHOTOCELL, 230W-400W ADJUSTABLE, 120~277V 5000K-BRONZE	1
LFL10-SF	SLIP FITTER FOR LFL10 SERIES	8
LFL10-T	TRUNNION MOUNT FOR LFL10 SERIES	8
LFL10-PM	POST MOUNT FOR LFL10 SERIES	12
LFL10-YK-300	YOKE MOUNT FOR LFL10 300W-400W	10
SFPMA	SLIP FITTER TO POST MOUNT ADAPTER FOR LFL10 SERIES	12

STABLE WAY



