Eaton CRL530R

Catalog Number: CRL530R

Eaton corrosion resistant locking receptacle, #14-10 AWG, 30A, Industrial, 125V, Back and side wiring, Yellow, Single, Corrosion resistant, L5-30, Two-pole, Three-wire, Thermoplastic

General specifications



Catalog Number

Eaton Arrow Hart corrosion resistant

CRL530R

locking receptacle

UPC

040893677156

Product Length/Depth

Product Height

1.54 in

4.19 in

Product Width

Product Weight

0.75 in

0.3 lb

NOM

Compliances

Certifications

RoHS Compliant

cULus Listed

Federal Specifications Classification W-

CSA certified

C375

UL Listed



Electrical Ratings

Amperage Rating

30A

NEMA configuration

L5-30

Operating temperature

-20 to 70 °C (-4 to 158 °F)

Torque rating

20 lbf-inch

Voltage rating

125 V

Wiring method

Back and side

Product Specifications

Allowable wire size

#14-10 AWG

Application

Industrial

Design type

Single receptacle

Device grade

Extra heavy-duty industrial specification grade

Number Of Poles

Two-pole

Number of gangs

Single-gang

Receptacle type

Locking

Type

Locking receptacle

Environmental Specifications

Environmental conditions

Corrosion resistant

Environmental resistance

Corrosion resistant

Material Specifications

Color

Yellow

Contact material

Nickel plated brass

Face/body material

Glass filled nylon

Material

Thermoplastic

Resources

Brochures

Complex environment devices brochure

Specifications and datasheets

Eaton Specification Sheet - CRL530R



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia