

Compression Lugs

One Hole - Short Barrel

Features

- Ideal for direct burial in earth or concrete and grounding applications
- Produced from high conductivity copper tubing and suitable for heavy duty applications
- Tin-plated to provide corrosion resistance
- Color coded

Applications


- Listed for 35 KV maximum when properly installed

Standard Material

- Copper

Standard Finish

- Tin plated



Catalog Number	UPC	Wire Size	Color Code	Bolt Size	Unit Carton	Ship Case	Weight/Case	Inches	
								A	B
2901	81614	#8	Red	10	100	1000	14	1.20	.42
2901A	81615	#8	Red	1/4"	100	1000	13	1.20	.42
2902	81616	#6	Blue	1/4"	100	1000	17	1.50	.42
2902A	81617	#6	Blue	5/16"	100	1000	17	1.50	.42
2903	81618	#4	Gray	1/4"	100	1000	20	1.50	.71
2903A	81619	#4	Gray	5/16"	100	1000	18	1.50	.71
2903B	81620	#4	Gray	3/8"	100	1000	18	1.50	.71
2905	81621	#2	Brown	3/8"	100	1000	28	1.80	.83
2905A	81622	#1	Green	3/8"	100	1000	35	1.83	.67
2906	81623	1/0	Pink	3/8"	50	500	21	1.83	.74
2907	81624	2/0	Black	3/8"	50	500	32	2.24	.81
2907A	81625	2/0	Black	1/2"	50	500	29	2.24	.81
2908	81626	3/0	Orange	3/8"	25	250	21	2.36	.90
2909	81627	4/0	Purple	1/2"	25	250	24	2.36	1
2909A	81804	250 MCM	Yellow	1/2"	25	250	30	2.48	1.09
2909B	81805	300 MCM	White	1/2"	25	250	33	2.49	1.19
2910	81628	350 MCM	Red	1/2"	20	200	33	2.61	1.28
2910A	81629	400 MCM	Blue	1/2"	10	100	24	3.95	1.39
2911	81806	500 MCM	Brown	5/8"	10	100	33	3.28	1.54
2911A	81807	600 MCM	Green	5/8"	5	50	24	3.50	1.72
2912	81630	750 MCM	Black	5/8"	5	50	35	4.37	1.90