SATCO NUVO

Project Name

Prepared By



Notes

General	
Status	Active
Watts	23W
HID Equivalent	100W
Volts	120V-277V
Shape	ED23.5
Base	Medium
ANSI Base	E26
Finish	Clear
CCT (Kelvin)	4000K
Temperature	Cool White
CRI	80+
Lumens	4000L
Beam Spread	320
Dimmable	Non-Dimmable
Hours Rated	50000
Product Category	LED HID
Technology	LED
Min Compartment Size	Length: 5.98 in. Width: 5.98 in. Height: 10.16 in.
Ballasting Requirements	Ballast Bypass
Electrical	
Operating Frequency	60Hz
Power Factor	0.9
Operating Position	Universal
Surge Protection	Built-in surge protection - 4KV
Operating Temperature	-30C (-22F) to +65C (+149F)
Physical	
MOL	7.6
MOD	2.95
Weight (lb.)	0.4
Additional Information	
Rated For Enclosed Fixture	Yes
IP Rating	IP65
Installation Notes	Not for use in vapor tight fixtures.
Warranty	5 Year Limited - Hi-Pro
Compliance	
Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating	Wet
DLC Approved	No
California Status	Lawful for sale in California
Title 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
RoHS Compliant FCC Compliant	Yes Yes

Safety Listing	cULus - Certified; cULus - Classified; cULus - Listed
ocation Rating	Wet
DLC Approved	No
California Status	Lawful for sale in California
itle 20 / 24 Status	Lawful for sale
RoHS Compliant	Yes
CC Compliant	Yes
DS Sheet	LED_Lamp