Project	Catalog #	Туре	
Prepared by	Notes	Date	



# **WaveLinx**

# **CAT Occupancy Ceiling Sensor** (OCS-C-P-\*)

Ceiling mount occupancy and daylight sensor

#### **Typical Applications**

Office • Education • Healthcare • Hospitality • Retail • Industrial · Manufacturing · Outdoor



# Interactive Menu

- Order Information page 2
- Additional Resources page 3
- Wiring Diagrams page 3
- Connected Systems page 5
- Product Warranty

### **Product Certification\***





- Meets latest ASHRAF 90.1 2019 requirements
- Meets latest IECC 2021 requirements
- Meets latest Title 24 2019 requirements Manufactured in an ISO 9001 certified factory

### **Product Features**







### Compatibility



### **Overview**

The Occupancy Ceiling Sensor with passive infrared and photocell that automatically control lights via CAT communication bus to compatible dimming and switching devices. These sensors detect the heat from people moving within the area to determine when the space is occupied. The sensor also detects the daylight coming into the space from the windows to determine when the fixtures near the windows should be dimmed.

The sensor then transmits the appropriate commands to the associated dimming and switching devices via the CAT communication bus to turn the lights on or off automatically to meet and exceed the local energy code.

### **Product Features & Benefits**

- Motion detection up to 12 ft mounting height Reduce energy consumption by turning lights on/off based on the space occupancy
- Built-in Photocell Reduce energy usage based on the daylight coming into the space
- LED Status Indicator Easily troubleshoot the sensor when required.
- Easy to configure / commission Remotely configurable through WaveLinx CAT mobile app





### **Order Information**

#### **Catalog Number**

Catalog Number	Description
OCS-C-P12	OCS-C Occupancy Ceiling Sensor, 1200 sqft
OCS-C-P06	OCS-C Occupancy Ceiling Sensor, 600 sqft

#### **Required Accessory**

The WaveLinx CAT network requires termination of the local CAT bus network on both ends.

#### **Catalog Number**

Catalog Number	Description
ACC-C-TP-6PK	ACC-C Canbus Termination Plug - 6PK

#### **Optional Accessories**

#### **Catalog Number**

Catalog Number	Description
GGRJ45-006-G	RJ45 cables 6 inches
GGRJ45-03-G	RJ45 cables 3 feet
GGRJ45-10-G	RJ45 cables 10 feet
GGRJ45-25-G	RJ45 cables 25 feet
GGRJ45-50-G	RJ45 cables 50 feet
GGRJ45-100-G	RJ45 cables 100 feet
GGRJ45-10P-G	RJ45 cables 10 feet plenum rated
GGRJ45-25P-G	RJ45 cables 25 feet plenum rated
GGRJ45-50P-G	RJ45 cables 50 feet plenum rated
GGRJ45-100P-G	RJ45 cables 100 feet plenum rated

### **Product Specifications**

### **Key Features**

- Daylight sensing and occupancy detection technologies combined into a single device
- All device settings (timers, sensitivity and groups) programmable through mobile app, no physical adjustments needed
- Ultra low profile and small diameter provides an aesthetically pleasing design
- Powered by the CAT local bus

#### Mechanical

Size: 3.6"H x 3.6"W x 1.4"D (91mm x 91mm x 36mm) Mounting: 4" octagon junction box or 3" hole in ceiling tile Color: White

**Coverage:** 600 or 1200 sq. ft. at 8' ceiling height **Occupancy Detection Technology:** Passive Infrared (PIR)

Lens Type: Multi-level Fresnel 360° Daylight Sensing Range: 0 to 100 lux

Daylight Sensing Coverage: Light input within 60° cone

#### Environmental:

- Operating temperature: 32°F to 104°F (0°C to 40°C)
  Operating relative humidity: 5% to 85% non-condensing
  Storage temperature: -22°F to 158°F (-30°C to 70°C)
- · For indoor use only

#### **Electrical**

Status Indicator: LED

Input Voltage: 9.5 - 22.5 VDC supplied by communication bus

Wiring: 18 AWG stranded PTFE plenum rated

### Network connection:

- CAT5 Solid Copper 24AWG
- T568B pin/pair assignment is recommended for all CAT5 cable

#### **Control Specification:**

· Communication Interface: CAT cable bus

### Standards/Ratings\*

- Class 2 Input
- FCC Part 15
- Manufactured in an ISO 9001 certified factory
- Meets ASHRAE Standard 90.1 requirements
- Meets IECC 2021 requirements
- · Meets CEC Title 24 requirements

### **Environmental Regulations:**

• RoHS

#### Warranty

Five year warranty standard







Download the WaveLinx CAT Mobile Application from either the Google Play or Apple Store®




### **Dimensional Details**


Sensor is designed to be installed into ceiling tile or onto a junction box.










# **Wiring Diagrams**






## Coverage






**Coverage Area** 600 sq. ft.

**Coverage Area** 1,200 sq. ft.



# **Typical Topology**





### **System Diagram:**


This diagram shows the main components of the WaveLinx connected lighting system with CAT and PRO devices.

The PRO devices communicate using wireless mesh technology based on the IEEE 802.15.4 standard. A PoE LAN connection for each WaveLinx Area Controller (WAC) is required for power and data access to the building lighting network.

The CAT devices communicate over the category 5 based communication bus and control the light fixtures using a relay (on/off) and 0-10V output (dim/raise).

WaveLinx Area Controllers (WAC) communicate with WaveLinx CORE Apps over the Ethernet network.









**Cooper Lighting Solutions** 

1121 Highway 74 South Peachtree City, GA 30269 P: 770-486-4800

www.cooperlighting.com