RIDGELINE® FULL BRIM

SIGNATURE STYLE, PROVEN PROTECTION

Experience top-notch protection with the Ridgeline® Full Brim hard hat. Its durable ABS shell provides superior impact resistance and lightweight comfort, while the full brim design ensures maximum coverage from environmental hazards. The innovative adjustable, swinging ratchet suspension allows the hard hat to sit lower on the head for a more comfortable fit. The ratchet suspension offers effortless adjustment, fitting sizes 6.5 to 8 securely.










'ENTED PTIONS S



FEATURES

Robust, Lightweight Shell: ABS shell ensures durable, lightweight protection

Complete Cover: Full brim design ensures maximum protection from environmental hazards while enhancing comfort and visibility

Accessory Compatibility (Vented Only): Universal accessory slots to add additional protection

Effortless Adjustment: 4 or 6-point swinging ratchet suspension easily adjusts to provide a perfect fit across all head sizes

Enhanced Ventilation (For Select Models): Strategically placed vents improve airflow and reduce heat buildup, providing cooler wear during extended use

Hygienic Solution: Replaceable sweatband promotes cleanliness and comfort

Engineered Toughness: Meets ANSI/ISEA Z89.1-2014 Type I, . certified for CAN/CSA Z94.1-2015 Type I to ensure durability and confidence in performance



RIDGELINE® FULL BRIM

SIGNATURE STYLE, PROVEN PROTECTION









NPTINNS

SUSPENSION

VARIATIONS

NON-VENTED

4-Point Ratchet Suspension 20 Variations				
	HP54110	White		
	HP54111	Black		
	HP54112	Gray		
	HP54113	Slate Gray		
	HP54116	Matte White Graphite Pattern		
	HP54116S	Shiny White Graphite Pattern		
	HP54117	Matte Black Graphite Pattern		
	HP54117S	Shiny Black Graphite Pattern		
	HP54118	Matte Copper Graphite Pattern		
	HP54120	Red		
	HP54121	Matte Red Graphite Pattern		
	HP54122	Matte Blue Graphite Pattern		
	HP54123	Matte Silver Graphite Pattern		

6-Point Ratchet Suspension | 5 Variations

HP56110	White
HP56120	Red
HP56130	Yellow
HP56135	Green
HP56160	Blue



HP6PTSUS-Transforms 4-point suspensions to 6-point for cap style and full brim hard hats



VENTED

4-Point Ratchet Suspension | 9 Variations

HP54110V	White
HP54111V	Black
HP54117V	Matte Black Graphite Pattern
HP54113V	Slate Gray
HP54130V	Yellow
HP54131V	Hi-Vis Lime
HP54135V	Green
HP54141V	Hi-Vis Orange

Blue

HP54160V

REPLACEMENT PARTS



HPRBANDR-Ridgeline cap style and full brim hard hat sweat suspension



HPR541-4-point ratchet suspension

MATERIALS

HP54124

HP54130 HP54131

HP54135

HP54141

HP54160 HP54170

Shell: ABS (Acrylonitrile Butadiene Styrene) Plastic Sweatband: Polyester + Polyurethane (PU) Foam

Matte Lime Graphite Pattern

Hi-Vis Lime

Hi-Vis Orange

Pink

Suspension: HDPE (Polypropylene) + High Impact Nylon

GENERAL SPECIFICATIONS

Weight: 378 gm
Shell Thickness: 1.7-4 mm
Dimensions: 31 x 27 x 15.2 cm
Suspension Adjust Sizing: 6.5 to 8
Suspension: Adjustable with Ratcheting Wheel

MARKINGS

Standard: ANSI/ISEA 789 1-2014 + CAN/CSA 794 1-2015

Type: Type I Full Brim Hard Hat

Class: Non-Vented - Class E (Electrical) Rated for 20,000 Volts, Vented – Class C (Conductive) Does Not Offer Electrical Protection – Class G (General) Rated for 2,200 Volts

LT: Low Temperatures Protection up to -22°F HT: High Temperatures Protection up to 140°F

HV: Meets All Requirements for High-Visibility (HP54131, HP54141, HP54131V, HP54141V)

Date Code: Indicates Month and Year Shell was Molded - Does Not Indicate Service Life.

Product markings may vary // Updated as of 10.25

PRODUCT GUIDELINES

Never alter or modify the shell or suspension system. Always use original replacement parts. Decals/stickers are acceptable if they do not affect a hard hat's protective rating or make it difficult to find damage.

Inspect your hard hat shell and suspension on a regular basis. Check for cracks or faulty parts each time it is to be used. If you notice any sign of damage, the faulty part should be discarded and immediately replaced. Inspect the hard hat each time before use and replace immediately if there is any sign of damage.

The service life of a hard hat begins when the hard hat is put into service. Maximum service life is 5 years for the shell and 1 year for the suspension, beginning immediately upon first use. If the hard hat has received a considerable strike, it should be replaced immediately, even if there is no visible damage. Only use genuine Pyramex accessories and replacement parts that have been approved for use with this helmet.

Clean only with mild soap and lukewarm water. DO NOT USE paints, chemicals, gasoline, or similar substances on the hard hat. If these substances are applied on the shell, its impact resistance and other features could be decreased and could be dangerous for the user.

Store hard hat in a cool place out of direct sunlight. Do not store in vehicles where the interior temperature can become extreme and cause deterioration of the hard hat.